

WAAS
CH **81805**
W33A

APP CRS
329°

Rwy Ldg
TDZE **195**
Apt Elev **219**

RNAV (GPS) RWY 33

WASHINGTON EXEC/STAFFORD RGNL (R.MN)

RNP APCH - GPS.

▼

Inop table does not apply to LPV all Cats. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Circling Rwy 15 NA at night.

MALS

MISSED APPROACH: Climb to 700 then climbing left turn to 3000 direct FALKO and hold, continue climb-in-hold to 3000.

AWOS-3PT 126.325	QUANTICO APP CON ★ 127.05 290.375	GCO 135.075	UNICOM 122.725 (CTAF)
----------------------------	---	-----------------------	---------------------------------

ELEV 219

TDZE 195

REIL Rwy 15
HIRL Rwy 15-33

	700	3000	FALKO	
CATEGORY	A	B	C	D
LPV DA	445-3/4 250 (300-3/4)			
LNAV/ VNAV DA	680-1 1/8 485 (500-1 1/8)			
LNAV MDA	680-3/4	485 (500-3/4)	680-1 1/8	485 (500-1 1/8)
CIRCLING	720-1 501 (600-1)	820-1 601 (700-1)	820-1 3/4 601 (700-1 3/4)	1040-2 3/4 821 (900-2 3/4)

STAFFORD, VIRGINIA
Amdt 2 16MAY24

WASHINGTON EXEC/STAFFORD RGNL (R.MN)
38°24'N - 77°27'W

RNAV (GPS) RWY 33