


WAAS CH 93844 W27A	APP CRS 267°	Rwy Idg TDZE 752 Apt Elev 752
--	------------------------	---

RNAV (GPS) RWY 27
BUFFALO-LANCASTER RGNL (BQR)


RNP APCH - GPS.	⚠ Rwy 27 helicopter visibility reduction below 1 SM NA. Baro-VNAV NA. ⚠ NA Use Buffalo Niagara Intl altimeter setting. Straight-in Rwy 27 at night, Circling Rwy 27 at night, operational VGSI required, remain on or above VGSI glidepath until threshold.	MISSED APPROACH: Climb to 1300 then climbing left turn to 3400 direct DMRIO and hold, continue climb-in-hold to 3400.
-----------------	--	---

BUF ASOS 135.35	BUFFALO APP CON 126.15 263.125	UNICOM 123.05 (CTAF) 0
---------------------------	--	---



ELEV 752	TDZE 752
-----------------	-----------------

	1300	3400	DMRIO	
				4 NM Holding Pattern
				DMRIO
				HEBTO 2500
				2500
				087° 6000
				267° 3400
				GP 3.00°
				TCH 40
				5.4 NM 5 NM
CATEGORY	A	B	C	D
LPV DA	1070-1	318 (400-1)		NA
LNAV/VNAV DA	1164-1 1/8	412 (500-1 1/8)		NA
LNAV MDA	1320-1	568 (600-1)		NA
CIRCLING	1320-1	568 (600-1)		NA



NE-2, 01 OCT 2026 to 29 OCT 2026

NE-2, 01 OCT 2026 to 29 OCT 2026