DOVER FIVE DEPARTURE (RNAV)

TOP ALTITUDE: ASSIGNED BY ATC

TAKEOFF MINIMUMS
Rwy 8: Standard with minimum climb of 394′ per NM to 2500.
Rwy 17: Standard with minimum climb of 265′ per NM to 2400.
Rwy 26: 300-1¾ or standard with minimum climb of 312′ per NM to 2000.
Rwy 35: Standard with minimum climb of 302′ per NM to 2500.

NOTE: Chart not to scale.

AUGUSTA DEP CON★
126.8 270.3
CLNC DEL
118.65
AUGUSTA TOWER★
118.7 (CTAF) 239.3

NOTE: DME/DME/IRU or GPS required.
NOTE: RADAR required for non-GPS equipped aircraft.
NOTE: RNAV 1.
NOTE: For turbojet aircraft during Masters golf tournament week.
NOTE: Do not exceed 250K until advised by ATC.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 8, 17, 26, 35: Climb heading assigned by ATC for vectors to BEANS, then on depicted route to DOVER, then on heading 156° for RADAR vectors. Thence. . . .

. . . .maintain altitude assigned by ATC. Expect clearance to filed altitude/flight level within 10 minutes after departure.

DOVER FIVE DEPARTURE (RNAV)
(DOVER5.DOVER) 28FEB19
AUGUSTA, GEORGIA
AUGUSTA RGNL AT BUSH FLD (AGS)
SE-4, 29 OCT 2026 to 26 NOV 2026