KATMN SIX DEPARTURE (RNAV)

(KATMN6.KATMN) 24MAY18

PHOENIX, ARIZONA
MESA GATEWAY (IWA)

TOP ALTITUDE: ASSIGNED BY ATC

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 12L/C/R: Climb heading 124° or as assigned by ATC. Thence. . . .
TAKEOFF RUNWAYS 30L/C/R: Climb heading 304° or as assigned by ATC. Thence. . . .

. . . .on RADAR vectors to ECLPS, then on track 111° to KATMN, then on (transition). Maintain ATC assigned altitude, expect filed altitude 3 minutes after departure.

PHASE TRANSITION (KATMN6.PHASE)

PHOENIX DEP CON
124.9 353.8
ATIS
133.5 270.275
CLNC DEL
135.05
GND CON
128.25 275.8
GATEWAY TOWER ★
120.6 289.4

304°
124°

ECLPS
FL180
*7600
111°
(47)
KATMN
FL180
*7600
093°
(48)
BOXXR
FL180
*9100
086°
(31)
PHASE

N

AL-74 (FAA)

NOTE: RNAV 1.
NOTE: Turbojets and turboprops only.
NOTE: RADAR required.
NOTE: GPS required.
NOTE: Aircraft departing KGEU and KGYR ATC assigned only.

TAKEOFF MINIMUMS
Rwys 12L/C/R: Standard with a minimum climb of 250′ per NM to 3100.
Rwys 30L/C/R: Standard.

NOTE: Chart not to scale.

(KATMN6.KATMN) 25051
KATMN SIX DEPARTURE (RNAV)
MESA GATEWAY (IWA)
PHOENIX, ARIZONA