VOR Y or TACAN Y RWY 15

CHARLESTON AFB/INTL (CHS)

VORTAC CHS	APP CRS	Rwy Ldg	9001
113.5	157°	TDZE	43
Chan 82		Apt Elev	46


DME required.


For inop ALS, increase S-15 Cat A/B visibility to RVR 5500 and Cat C/D visibility to RVR 6000.

ALSF-2


MISSED APPROACH: Climb to 500 then climbing left turn to 3500 on CHS VORTAC R-055 to WANDO/CHS 13 DME and hold, continue climb-in-hold to 3500.

D-ATIS	CHARLESTON APP CON	CHARLESTON TOWER	GND CON
124.75	120.7 306.925	126.0 239.0	121.9 348.6





VGSI and descent angles not coincident (VGSI Angle 3.00°/TCH 54).



CATEGORY	A	B	C	D
S-15	460/24	417 (500-½)	460/40	417 (500-¾)
CIRCLING	540-1	494 (500-1)	540-1½ 494 (500-1½)	740-2¼ 694 (700-2¼)

TDZL/RCLS Rwy 15
REIL Rwys 3 and 21
HIRL Rwys 3-21 and 15-33

SE-2, 29 OCT 2026 to 26 NOV 2026
SE-2, 29 OCT 2026 to 26 NOV 2026