RNAV (RNP) W RWY 13R


DALLAS LOVE FLD (DAL)

APP CRS	Rwy Ldg	8310
133°	TDZE	478
	Apt Elev	487

For uncompensated Baro-VNAV systems, procedure NA below -5°C (23°F) or above 54°C (130°F). Simultaneous approach authorized. RF required. GPS required. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MISSED APPROACH: Climb to 3000 direct ENAVE and on track 151° to TACKE and hold.

D-ATIS	LONE STAR APP CON	LOVE TOWER	GND CON
120.15	124.3 282.275 (N) 125.2 343.65 (S)	123.7 239.3	121.75 348.6




ELEV 487 D TDZE 478

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 52).


3000	ENAVE	tr 151°	TACKE

See planview for multiple IF locations.



CATEGORY	A	B	C	D
RNP 0.20 DA		781/50	303 (300-1)	
RNP 0.25 DA		833/60	355 (400-1¼)	
RNP 0.30 DA		929-1½	451 (500-1½)	

AUTHORIZATION REQUIRED



TDZL/RCLS Rwys 13L and 31L
HIRL Rwys 13L-31R, and 13R-31L

SC-2, 29 OCT 2026 to 26 NOV 2026
SC-2, 29 OCT 2026 to 26 NOV 2026