RNAV (GPS) RWY 23R

PIEDMONT TRIAD INTL (GSO)


WAAS CH 90315 W23B	APP CRS 234°	Rwy Ldg 9000 TDZE 864 Apt Elev 926

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). DME/DME RNP-0.3 NA. Simultaneous approach authorized with ILS or LOC RWY 23L, ILS RWY 23L CAT (II). LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.


MALSR (A5)

MISSED APPROACH: Climb to 2500 direct JEVEN and hold.


D-ATIS	GREENSBORO APP CON	GREENSBORO TOWER	GND CON	CLNC DEL
128.55	124.35 269.225 (250°-049°) 126.6 327.075 (050°-249°)	119.1 290.325	121.9 348.6	121.75







CATEGORY	A	B	C	D
LPV DA	1064/18 200 (200-½)			
LNAV/VNAV DA	1414-1½ 550 (500-1½)			
LNAV MDA	1340/24 476 (500-½)		1340/50 476 (500-1)	
CIRCLING	1440-1 514 (600-1)		1700-2¼ 774 (800-2¼)	1700-2½ 774 (800-2½)



TDZ/CL Rwys 5L, 23R and 23L
REIL Rwy 32
HIRL Rwys 14-32, 5R-23L and 5L-23R

SE-2, 29 OCT 2026 to 26 NOV 2026
SE-2, 29 OCT 2026 to 26 NOV 2026