RNAV (RNP) Y RWY 12L

MINNEAPOLIS-ST PAUL INTL/WOLD-CHAMBERLAIN (MSP)

APP CRS	Rwy Ldg	7620
121°	TDZE	841
	Apt Elev	842


RNP AR APCH - GPS. Authorization required. From INGLS: RF.


For uncompensated Baro-VNAV systems, procedure NA below -20°C or above 54°C. Simultaneous approach authorized. For inop ALS, increase RNP 0.15 visibility all Cats to RVR 4500, and RNP 0.30 visibility all Cats to RVR 6000.

ALSF-2


MISSED APPROACH: Climb to 1300 then climbing left turn to 3000 direct KANAC and hold.

D-ATIS	MINNEAPOLIS APP CON	MINNEAPOLIS TOWER	GND CON
135.35 239.275	118.725 335.65 (35)	123.675 273.55 (17-35)	121.8 348.6 (N)
	119.3 335.65 (4-22, 12L-30R, 17)	123.95 273.55 (12L-30R)	121.9 348.6 (S)
	126.95 335.65 (12R-30L)	126.7 273.55 (4-22, 12R-30L)	127.925 348.6 (W)





HIRL all rwys
REIL Rwy 17
TDZL/RCLS Rwys 12L, 12R, 30L, and 35



CATEGORY	A	B	C	D
RNP 0.15 DA	1152/24 311 (400-½)			
RNP 0.30 DA	1243/40 402 (500-¾)			

AUTHORIZATION REQUIRED

NC-1, 29 OCT 2026 to 26 NOV 2026
NC-1, 29 OCT 2026 to 26 NOV 2026