WAAS CH 87012 W01A	APP CRS 003°	Rwy Ldg 7441	TDZE 479	Apt Elev 534

RNAV (GPS) RWY 1

PRESQUE ISLE INTL (PQI)

RNP APCH - GPS.

T A -36°C

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to 1⅜ SM and LNAV Cats C and D to 1⅝ SM. Circling Rwy 10 NA at night. When local altimeter setting not received, use HUL altimeter setting: increase LPV DA to 769 feet; increase LNAV/VNAV DA to 1062 feet and all visibilities ¼ SM; increase all MDAs 100 feet and LNAV visibility Cats C and D ¼ SM, and Circling visibility Cat C ½ SM and Cat D ¼ SM. Baro-VNAV and VDP NA when using HUL altimeter setting. For inop ALS when using HUL altimeter setting, increase LPV all Cats visibility to ⅞ SM, and LNAV Cats C and D to 1⅞ SM.

MALSR

MISSED APPROACH: Climb to 3000 direct VEGGS and hold.

AWOS-3PT	BOSTON CENTER	CLNC DEL	UNICOM	
118.025	124.75 239.05	121.6	122.8 (CTAF)	122.6 L

MISSED APCH FIX

4 NM 183° 003° VEGGS

RW01

787±

NANKE 3 NM to RW01

OBKOE 4.1 NM to RW01

1161±

(FAF) PITRE

2700 003° (12.2)

CANADA / UNITED STATES

30 NM to TECOG

3300

183°

TECOG

273°

30 NM to AHIZI

4400

183°

10 NM

3200

AHIZI

093°

(IAF) TECOG

3200 NoPT

273° (9)

273°

093°

CORAC

3200

3900

10 NM

30 NM to CORAC (NoPT)

3200 NoPT

093° (9)

(IF/IAF) CORAC

183°

003°

(IAF) AHIZI

4 NM

HOLD 6000 3200

ELEV 534 D TDZE 479

7441 X 150

654

1.1 % UP

6000 X 100

19

28

10

1

REIL Rwy 19 L

HIRL Rwy 1-19 L

MIRL Rwy 10-28 L

003°

3000 VEGGS

OBKOE 4.1 NM to RW01

PITRE

CORAC

4 NM Holding Pattern

183° 6000

003° 3200

NANKE 3 NM to RW01

2700

003°

1.7 NM to RW01

RW01

1460

1800

2700

GP 3.00° TCH 50

1.7 NM 1.3 NM 1.1 NM 2.8 NM 12.2 NM

CATEGORY	A	B	C	D
LPV DA	679-½ 200 (200-½)			
LNAV/VNAV DA	972-1 493 (500-1)			
LNAV MDA	1040-½ 561 (600-½)		1040-1¼ 561 (600-1¼)	
CIRCLING	1180-1 646 (700-1)		1320-2¼ 786 (800-2¼)	1380-2¾ 846 (900-2¾)

NE-1, 29 OCT 2026 to 26 NOV 2026
NE-1, 29 OCT 2026 to 26 NOV 2026