RNAV (RNP) W RWY 35L

RENO/TAHOE INTL (RNO)

APP CRS	Rwy Ldg	10011
347°	TDZE	4410
	Apt Elev	4415

RNP AR APCH - GPS.

For uncompensated Baro-VNAV systems, procedure NA below -9°C or above 35°C .

-13°C


MALSR


MISSED APPROACH: Climb to 11000 on track 347° to TAKLE and hold, continue climb-in-hold to 11000.
*Missed approach requires minimum climb of 300 feet per NM to 7140.

D-ATIS	NORCAL APP CON	RENO TOWER	GND CON
135.8 363.0	119.2 279.55 126.3 353.9	118.7 257.8	121.9 348.6

MISSED APCH FIX

7 NM 167° 347° TAKLE






CATEGORY	A	B	C	D
RNP 0.10 DA*	4736-½ 326 (400-½)			
RNP 0.30 DA	5349-2 939 (1000-2)			

AUTHORIZATION REQUIRED

ELEV 4415 D TDZE 4410

HIRL Rwys 17R-35L and 17L-35R
REIL Rwys 8, 17L, 26, and 35R
MIRL Rwy 8-26



SW-4, 29 OCT 2026 to 26 NOV 2026
SW-4, 29 OCT 2026 to 26 NOV 2026