OZARK EIGHT DEPARTURE


(OZARK8.STL) 07OCT21

ST. LOUIS, MISSOURI

ST LOUIS LAMBERT INTL (STL)

TOP ALTITUDE:
(JETS) 5000/(PROPS) 3000

D-ATIS
125.025 379.925
CLNC DEL
119.5 363.1
CPDLC
GND CON
121.9 348.6 (Inbound)
121.65 377.175 (Outbound)
118.925 227.125 (Rwy 11/29)
ST LOUIS TOWER
120.05 284.6 (12L/30R, 24)
118.5 257.7 (12R/30L)
132.475 239.275 (6, 11/29)
ST. LOUIS DEP CON
128.1 307.05



NOTE: DME and RADAR required.

DEPARTURE ROUTE DESCRIPTION

Climb on assigned heading for vector to appropriate route.
JETS: Maintain 5000 or assigned altitude, Thence. . . .
PROPS: Maintain 3000 or assigned altitude, Thence. . . .

. . . . (transition). Expect filed altitude 10 minutes after departure.

HALLSVILLE TRANSITION (OZARK8.HLV): From over STL VORTAC on STL R-281 to CABIT, then on STL R-281 and HLV R-095 to HLV VORTAC.

TAKEOFF MINIMUMS
Rwys 6, 12L/R, 24, 29: Standard.
Rwy 11: 200-1 or standard with minimum climb of 370′ per NM to 900.
Rwy 30L: 200-1 or standard with minimum climb of 245′ per NM to 800.
Rwy 30R: 200-1⅜ or standard with minimum climb of 230′ per NM to 800.

NOTE: Chart not to scale.

(OZARK8.STL) 26246

OZARK EIGHT DEPARTURE

AL-360 (FAA)

ST. LOUIS, MISSOURI

ST LOUIS LAMBERT INTL (STL)