SAN ANTONIO, TEXAS

ILS or LOC/DME Y RWY 34

LOC I-OSQ	APCH CRS	Rwy ldg 11,550 / TDZE 660 / Arpt Elev 690
110.7	338°	

[USAF] KELLY FLD (KSKF)

* When ALS inop, increase RVR to 40 and vis to ¾ mile.
** When ALS inop, increase RVR to 55 and vis to 1 mile.
*** Circling not authorized E of Rwy 16-34.

ALSF-1

†MISSED APPROACH: Climb to 2500 via KSY TACAN R-331 until 9 DME, cross 9 DME at 2500, then continue climb to 3000 to IDEEL/12 DME. Expect ATC instuctions.

ATIS	SAN ANTONIO APP CON	TOWER	GND CON
120.45 273.5	118.05 353.5	124.3 322.35	121.8 289.4

† Non-TACAN equipped aircraft expect alternate missed approach instructions.

1171 2049

R-331 IDEEL KSY 12

KSY 9

KELLY
Chan 57 KSY
(112.0)

1106

LOCALIZER 110.7
I-OSQ

1021 867

JETKA KSY 1.9

751 LANCO KSY 4

ICCAP KSY 6

1639

338° 2200

158°

1098 1608

(IF/IAF) CEPRO KSY 15

HOLD 2700 265° 339° 159° R-159

KSY 20

EMERG SAFE ALT 100 NM 4200

MSA KSY 2.5 NM
180°
4200
090° 3200
2600
360°

ELEV 690 TDZE 660

2500 KSY R-331 9
KSY R-331 9
3000 IDEEL KSY 12

ICCAP KSY 6
CEPRO KSY 15
KSY 20
159° 2700
338° 339°
VGSI and descent angles not coincident. (VGSI Angle 3.02/TCH 93)
GS 3.00°
TCH 60
LANCO KSY 4
2200
JETKA KSY 1.9
1100
2200

0.5 NM 2.1 NM 2.1 NM

CATEGORY	A	B	C	D	E
S-ILS 34*	860/24		200	(200-½)	
S-LOC 34**	1020/24	360 (400-½)	1020/30	360 (400-⅝)	
CIRCLING ***	1200-1 510 (600-1)	1280-1 590 (600-1)	1340-1¾ 650 (700-1¾)	1900-3 1210 (1300-3)	

707 TWR 780 727

11,550 × 150 0.3% UP

857 855 34 713 338°

HIRL Rwy 16-34

SAN ANTONIO, TEXAS 29° 23'N-98° 35'W KELLY FLD (KSKF)

Amdt 2 17APR25

ILS or LOC/DME Y RWY 34

SC-3, 29 OCT 2026 to 26 NOV 2026