ILS or LOC RWY 5

SPARTANBURG DOWNTOWN MEML/SIMPSON FLD (SPA)

LOC/DME I-SPA	APP CRS	Rwy Ldg	5852
109.1	047°	TDZE	802
Chan 28		Apt Elev	802

DME required.

For inop ALS, increase S-LOC 5 Cats C/D visibility to 1 SM.

MALSR

MISSED APPROACH: Climb to 1300 then climbing left turn to 3000 direct SPA VORTAC and hold, continue climb-in-hold to 3000.

AWOS-3	GREER APP CON ★	CLNC DEL	UNICOM
133.925	119.4 350.2	120.55	123.0 (CTAF) L

Procedure NA for arrival on SPA VORTAC airway radials 231 CW 269.

SPARTANBURG 115.7 SPA Chan 104

2500 to FREST 212° (17.8)

R-194–014° 194°

LOCALIZER 109.1 I-SPA Chan 28

899±

LOM JUDKY 521 GM

(IF/IAF) FREST INT I-SPA 11.9

276°

2100

047° (6.8)

VETPY I-SPA 5.1

047°

1 min

227°

227°

HOLD 5200 2500

MSA SPA 25 NM

5200

224°

044°

2900

ELEV 802 D TDZE 802

One Minute Holding Pattern

FREST INT I-SPA 11.9

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 45).

1300 3000 SPA

*LOC only.

5200 2500 227° 047°

047°

VETPY I-SPA 5.1

2100

*I-SPA 2.1

I-SPA 1.1

GS 3.00° TCH 50

2100

6.8 NM 2.9 NM 1 NM

CATEGORY	A	B	C	D
S-ILS 5	1002-¾ 200 (200-¾)			
S-LOC 5	1160-¾ 358 (400-¾)			
CIRCLING	1320-1 518 (600-1)		1380-1½ 578 (600-1½)	1420-2 618 (700-2)

862

5852 X 100

5

23

047°

HIRL Rwy 5-23 L

REIL Rwy 23 L

SE-2, 29 OCT 2026 to 26 NOV 2026

SE-2, 29 OCT 2026 to 26 NOV 2026