ILS or LOC RWY 20

WALLA WALLA RGNL (ALW)

LOC I-ALW	APP CRS	Rwy Ldg	6527
111.7	202°	TDZE	1194
		Apt Elev	1194

DME required.

T A DME from ALW VOR/DME. Simultaneous reception of I-ALW and ALW VOR/DME required. For inop ALS, increase S-LOC 20 Cat C/D visibility to 2½ SM.
#RVR 1800 authorized with use of FD or AP or HUD to DA (NA when using Pendleton altimeter setting).

MALSR

MISSED APPROACH: Climb to 1800 then climbing right turn to 4000 on heading 346° and ALW VOR/DME R-314 to BACUN INT/ ALW 15.4 DME and hold.

ASOS	SPOKANE APP CON ★	WALLA WALLA TOWER ★	GND CON	UNICOM
135.875	133.15 379.15	118.5 (CTAF) L 289.4	121.6 289.4	122.95

ALTERNATE MISSED APCH FIX: BUTOC PSC 40; 113.75 PSC; R-070; Chan 84(Y); 070°; 250°

MSA ALW 25 NM: 3500; 181°; 091°; 7600; 5000; 001°

(IAF) HOLOW INT ALW 17.8

114.45 MQG R-246 Chan 91(Y)

RENGO MQG 40.6; 6200; 246°; (8)

022°

(IAF) BUTOC PSC 40

4600 to RIRRO 117° hdg (3.9) and 202° (2)

4600 to RIRRO 202° (5.5)

BACUN ALW 15.4; 134°; 314°; R-070; 113.75 PSC; Chan 84(Y)

R-314

3600; 202°; (3.6); (IF) RIRRO ALW 12.3

3200 (1.6)

AL LOM

ZALBI ALW 8.7

COSUV ALW 7.2

HIVOP ALW 4

1800; 1719±

LOCALIZER 111.7 I-ALW

WALLA WALLA 116.4 ALW Chan 111

2000; 3000; 4000

ELEV 1194 D TDZE 1194

202°; 20; 6527 X 150; TWR; 0.6% UP

REIL Rwy 2 L

HIRL Rwy 2-20 L

1800; 4000 hdg 346°; ALW R-314; BACUN

ALW 1; ALW 3.3; HIVOP ALW 4; COSUV ALW 7.2; ZALBI ALW 8.7; RIRRO ALW 12.3; 3200; 2400; 3600; 4600; 202°; GS 3.00°; TCH 50

2.3 NM; 0.7 NM; 3.1 NM; 1.6 NM; 3.6 NM

CATEGORY	A	B	C	D
S-ILS 20#	1394/24 200 (200-½)			
S-LOC 20	1980/24 786 (800-½)	1980/40 786 (800-¾)	1980-1¾ 786 (800-1¾)	
CIRCLING	1980-1 786 (800-1)	1980-1¼ 786 (800-1¼)	2120-2¾ 926 (1000-2¾)	2300-3 1106 (1200-3)

NW-1, 29 OCT 2026 to 26 NOV 2026
NW-1, 29 OCT 2026 to 26 NOV 2026