RNAV (GPS) RWY 22


TUSCALOOSA NTL (TCL)

WAAS	APP CRS		
CH **81918**	**221°**	Rwy Ldg	**6498**
W22A		TDZE	**164**
		Apt Elev	**170**

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 48°C (118°F). DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Birmingham altimeter setting: increase LPV DA to 760 feet and all visibilities ½ SM; increase LNAV/VNAV DA to 937 feet and all visibilities ¾ SM; increase all MDAs 180 feet and visibility LNAV Cats C and D ½ SM and Circling Cat C ¾ SM and Cat D ½ SM. Baro-VNAV and VDP NA when using Birmingham altimeter setting. Circling Rwy 12, 30 NA at night.

MISSED APPROACH: Climb to 2500 direct ROBND and left turn on track 131° to MOVIL and on 050° track to OKW VORTAC and hold.

ASOS	BIRMINGHAM APP CON	TUSCALOOSA TOWER ★	GND CON	UNICOM
132.825	**120.15 269.25**	**126.3** (CTAF) L **256.7**	**121.8 257.95**	**122.95**



CATEGORY	A	B	C	D
LPV DA	582-1½		418 (500-1½)	
LNAV/VNAV DA	759-2		595 (600-2)	
LNAV MDA	700-1	536 (600-1)	700-1½ 536 (600-1½)	700-1¾ 536 (600-1¾)
CIRCLING	720-1 550 (600-1)	800-1 630 (700-1)	960-2¼ 790 (800-2¼)	960-2½ 790 (800-2½)

SE-4, 29 OCT 2026 to 26 NOV 2026