ILS or LOC RWY 13

SAN MARCOS RGNL (HYI)

LOC I-RUM	APP CRS	Rwy Ldg	5601
108.7	126°	TDZE	593
		Apt Elev	595

ADF required.

T NA Circling NA for Cat E southwest of Rwy 13-31. Inop table does not apply to S-ILS 13 all Cats. For inop ALS, increase S-LOC 13 Cat C/D/E visibility to 1⅞ SM.

MALS

MISSED APPROACH: Climb to 2000 then climbing left turn to 3200 direct GARYS LOM/INT and hold.

ATIS	AUSTIN APP CON	SAN MARCOS TOWER ★	GND CON
120.825	119.0 370.85	126.825 (CTAF) L	120.125

ALTERNATE MISSED APCH FIX

113.8 STV Chan 85 R-040 105° 285° R-105 BETTI STV 36.8 116.8 SAT Chan 115

CENTEX 112.8 CWK Chan 75

Procedure NA for arrival on CWK VORTAC airway radials 222 CW 271.

3700 215° (33.3) R-215 306° 171° 351° 126° 306° 1009±

113.8 STV Chan 85 R-105

MSA RU 25 NM 3100

BETTI STV 36.8

LOM/IAF GARYS 272 RU GARYS INT

LOCALIZER 108.7 I-RUM

R-040

3500 047° (32.7)

116.8 SAT Chan 115

Procedure NA for arrival on SAT VORTAC airway radials 002 CW 081.

SAN ANTONIO 116.8 SAT Chan 115

ELEV 595 TDZE 593

126° 17 13 5601 X 100 5214 X 100 8 6330 X 100 26 0.4% UP 0.4% UP 35 TWR

RU LOM GARYS INT

Remain within 15 NM

306° 2441 3200 126° 2700

GS 3.00° TCH 57

5.5 NM

2000 3200 RU

CATEGORY	A	B	C	D	E
S-ILS-13	793-¾ 200 (200-¾)				
S-LOC-13	1260-¾ 667 (700-¾)		1260-1¾ 667 (700-1¾)		
CIRCLING	1260-1 665 (700-1)		1260-1⅞ 665 (700-1⅞)	1320-2¼ 725 (800-2¼)	1340-2¾ 745 (800-2¾)

MIRL Rwys 8-26, 13-31, and 17-35 L

FAF to MAP 5.5 NM

Knots	60	90	120	150	180
Min:Sec	5:30	3:40	2:45	2:12	1:50

SC-3, 29 OCT 2026 to 26 NOV 2026
SC-3, 29 OCT 2026 to 26 NOV 2026