PEORIA, ILLINOIS

HI-VOR Y or TACAN Y RWY 31

VORTAC PIA	APCH CRS	Rwy ldg	10,104
115.2	281°	TDZE	650
Chan 99		Arpt Elev	661

[USAF] GENERAL DOWNING - PEORIA INTL (KPIA)

DME required. RADAR required for procedure entry.

* Straight-in Rwy 31, Circling Rwy 13-31 not authorized at night.

MALSR

MISSED APPROACH: Climb to 2800, direct PIA VORTAC and hold. Continue climb-in-hold to 2800. (TACAN aircraft: continue on PIA R-269 to LOGOS/PIA 17.5 DME and hold west, right turn 089° inbound).

ATIS	SAINT LOUIS APP CON	PEORIA TOWER	GND CON
126.1 282.2	125.8 269.2	124.0 353.85	121.85 348.6

ALTERNATE MISSED APPROACH FIX
LOGOS
PIA 17.5
089°
230K
269°
115.2 PIA
R-269
Chan 99

PEORIA
115.2 PIA
Chan 99

(a) 211° (c)
101° (b)
031° (c)

R-275
095°
275°
830±
WELOT
PIA
8.6
769
1340
1349
1115
1787
2600
1000
FISHR
PIA 11.1
1270
(IF)
LIVDE
PIA 17.2
2700
281°
10,000
KOCES
PIA 25
HOLD
17,500
14,000
101°
265K
281°
R-101
(IAF)
MERKY
RADAR
PIA 36.2
14,000

If local altimeter setting not received, use Logan County altimeter setting.

MSA PIA 25 NM
180°
2300
2800
360°

EMERG SAFE ALT 100 NM 3300

ELEV 661 D TDZE 650

2800 PIA

LIVDE PIA 17.2
FISHR PIA 11.1
WELOT PIA 8.6
PIA 5.1
2700
281°
2600
1800
3.00°
TCH 55
3.5 NM
2.5 NM

682
TWR 755
13
31
10,104 x 150
8004 x 150
709
692
281°

CATEGORY	C	D	E
S-31*	1040/60	390 (400-1⅛)	
CIRCLING*	1180-1½ 519 (600-1½)	1400-2¼ 739 (800-2¼)	1680-3 1019 (1100-3)
LOGAN COUNTY ALTIMETER MINIMA			
S-31*	1140-1⅜	490 (500-1⅜)	
CIRCLING*	1280-1¾ 619 (700-1¾)	1500-2¾ 839 (900-2¾)	1780-3 1119 (1200-3)

HIRL all rwys

EC-3, 29 OCT 2026 to 26 NOV 2026
EC-3, 29 OCT 2026 to 26 NOV 2026