WAAS	APP CRS	Rwy Ldg 7201
CH 45714	094°	TDZE 771
W09A		Apt Elev 782

RNAV (GPS) RWY 9


BISHOP INTL (FNT)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inop ALS, increase LNAV Cat C/D visibility to 1⅜ SM.
**RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR


MISSED APPROACH: Climb to 3000 direct JUBUG and on track 099° to KATTY and hold.

ATIS	GREAT LAKES APP CON ★	FLINT TOWER ★	GND CON	UNICOM
133.15	118.8 257.9	126.3 (CTAF) L 257.9	121.9	122.95




EC-1, 29 OCT 2026 to 26 NOV 2026

EC-1, 29 OCT 2026 to 26 NOV 2026



CATEGORY	A	B	C	D
LPV DA **	971/24 200 (200-½)			
LNAV/VNAV DA	1227/50 456 (500-1)			
LNAV MDA	1260/24 489 (500-½)		1260/50 489 (500-1)	
CIRCLING	1260-1 478 (500-1)	1300-1 518 (600-1)	1300-1½ 518 (600-1½)	1520-2¼ 738 (800-2¼)



HIRL Rwys 9-27 and 18-36 L
REIL Rwy 18 and 36 L