RNAV (RNP) Z RWY 9

CINCINNATI/NORTHERN KENTUCKY INTL (CVG)

APP CRS	Rwy Ldg	11640
096°	TDZE	883
	Apt Elev	896

RNP AR APCH - GPS. Authorization required. From FLOTT or IDULE: RF.

For uncompensated Baro-VNAV systems, procedure NA below -13°C or above 54°C.

MALSR

MISSED APPROACH: Climb to 3000 direct BLOCK and on track 138° to CALIF and hold.

D-ATIS	CINCINNATI APP CON	CINCINNATI TOWER	GND CON
134.375	119.7 363.15 (090°-269°) 123.875 363.15 (270°-089°)	118.975 360.85 (18L/36R) 118.3 (9/27, 18C/36C) 133.325 (18R/36L)	121.7

MISSED APCH FIX
4 NM
111°
291°
CALIF

(IAF) ACHOO 7000 210K
3500 138° (12.7)
(IAF) BABGE 8000
3500 124° (14)
5000 277° (3.1)
HAPON
(IF) IDULE 6000 210K
2500 (8.2)
(IF) SEMSE
(FAF) KAVME
RW09
BLOCK
3500 096° (4.8)
(IAF) JADOP
2500 096° (3.3)
096° (4.9)
138° (10)
MSA RW09 25 NM
3000
2500 (8.2)
(IF) FLOTT 6000 210K
3500 058° (13.8)
GEHDI
5000 276° (3.1)
(IAF) CALFS 8000

ELEV 896 D TDZE 883

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 70).

3000	BLOCK	tr 138°	CALIF

KAVME
2500
2500
096°
RW09
GP 3.00°
TCH 52
See planview for multiple IF locations.
4.9 NM

CATEGORY	A	B	C	D
RNP 0.18 DA		1205/26	322 (400-½)	
RNP 0.30 DA		1275/35	392 (400-⅝)	

AUTHORIZATION REQUIRED

18R
18C
18L
8000 X 150
10000 X 150
12001 X 150
0.3% DOWN
6% UP
36L
TWR
27
096°
36C
36R

HIRL all rwys
TDZL/RCLS all rwys except 27

SE-1, 29 OCT 2026 to 26 NOV 2026

SE-1, 29 OCT 2026 to 26 NOV 2026