WAAS	APP CRS	Rwy Ldg	6145
CH 53631	218°	TDZE	68
W22A		Apt Elev	75

RNAV (GPS) RWY 22
ATLANTIC CITY INTL (ACY)

RNP APCH - GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -14°C (7°F) or above 54°C (130°F). Rwy 22 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 600 then climbing right turn to 2000 direct TUBER and hold.

ATIS	ATLANTIC CITY APP CON	ATLANTIC CITY TOWER	GND CON
125.725 316.15	124.6 327.125	120.3 239.0	121.9 284.6

RADAR REQUIRED WHEN R-5002B IS ACTIVE.

R-5002C
R-5002A and F
R-5002B
R-5002B and F

(IAF) PIDVE
1800
123° (6)
(IF) KOPCE
1600
203° (3.9)
FLDER
(FAF) EFEWY
1100
203° (2.1)
218°
218
RW22

CEDAR LAKE VCN
1800
077°
(16.8)

Procedure NA for arrival on VCN VORTAC airway radials 066 CW 160.

MSA RW 22 25 NM
2100

TUBER
017°
197°
6 NM

ELEV 75 D TDZE 68

218°

TWR
6145 X 150
10001 X 150
22
4
31

600 2000 TUBER

1.3 NM to RW22
RW22
218°
EFEWY
1100
1100
FLDER
1600
203°
KOPCE
1800
GP 3.00°
TCH 51

1.3 NM 1.8 NM 2.1 NM 3.9 NM

CATEGORY	A	B	C	D	E
LPV DA	364-1 296 (300-1)				
LNAV/VNAV DA	356-⅞ 288 (300-⅞)				
LNAV MDA	520-1 452 (500-1)		520-1⅜ 452 (500-1⅜)		
CIRCLING	540-1 465 (500-1)	600-1 525 (600-1)	620-1½ 545 (600-1½)	640-2 565 (600-2)	760-2½ 685 (700-2½)

TDZL/RCLS Rwy 13
HIRL Rwys 4-22 and 13-31
REIL Rwy 31

NE-2, 29 OCT 2026 to 26 NOV 2026
NE-2, 29 OCT 2026 to 26 NOV 2026