RNAV (GPS) RWY 24

MARTHA'S VINEYARD (MVY)


WAAS CH 48804 W24A	APP CRS 236°	Rwy Ldg 5504	TDZE 63	Apt Elev 67

T A For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -14°C (7°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Hyannis altimeter setting and increase all DA 54 feet and all MDA 60 feet; increase LNAV/VNAV all Cats visibility to RVR 5200; increase LNAV Cats C/D visibility to RVR 5000; increase Circling visibility Cats C to 2 miles and D to 2 ½ mile. For inop MALSR, increase LNAV/VNAV all Cats visibility to 1⅜ mile. For inop MALSR using Hyannis altimeter setting, increase LPV all Cats visibility to RVR 4000, LNAV/VNAV all Cats visibility to 1⅝ mile and increase LNAV Cats C/D visibility to 1⅜ mile. VDP and Baro-VNAV NA when using Hyannis altimeter setting. Night landing: Rwy 15 NA. ** RVR 1800 authorized with use of FD or AP or HUD to DA, NA when using Hyannis altimeter setting.


MALSR


MISSED APPROACH: Climb to 500 then climbing left turn to 2500 direct CLAMY and hold.

ATIS	BOSTON APP CON	VINEYARD TOWER★	GND CON	UNICOM
126.25	133.75	121.4 (CTAF) L	124.35	122.95



ELEV 67 D TDZ 63





CATEGORY	A	B	C	D
LPV DA	** 263/24		200 (200-½)	
LNAV/VNAV DA	480/47		417 (500-1)	
LNAV MDA	500/24	437 (500-½)	500/40	437 (500-¾)
CIRCLING	500-1 433 (500-1)	540-1 473 (500-1)	700-1¾ 633 (700-1¾)	780-2¼ 713 (800-2¼)

HIRL Rwy 6-24 L
MIRL Rwy 15-33 L
REIL Rwy 6
REIL Rwy 33 L

NE-1, 29 OCT 2026 to 26 NOV 2026
NE-1, 29 OCT 2026 to 26 NOV 2026