RNAV (GPS) Y RWY 15R

BALTIMORE/WASHINGTON INTL THURGOOD MARSHALL (BWI)

WAAS	APP CRS	Rwy Ldg	8301
CH 66007	155°	TDZE	138
W15B		Apt Elev	143


RNP APCH - GPS.


For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -11°C or above 54°C. Simultaneous approach authorized with Rwy 15L. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 6000. * RVR 1800 authorized with use of FD or AP or HUD to DA.


MALSR

MISSED APPROACH: Climb to 2500 direct JANNS and hold.

D-ATIS	POTOMAC APP CON	BALTIMORE TOWER	GND CON
115.1 127.8	119.0 282.275 (020°-100°) 119.7 290.475 (131°-180°) 124.55 317.425 (101°-130°) 128.7 307.9 (181°-019°)	119.4 257.8	121.9







CATEGORY	A	B	C	D
LPV DA	*338/24 200 (200-½)			
LNAV/VNAV DA	557/40 419 (500-¾)			
LNAV MDA	560/24 422 (500-½)		560/40 422 (500-¾)	
CIRCLING	640-1 497 (500-1)	660-1 517 (600-1)	700-1½ 557 (600-1½)	880-2¼ 737 (800-2¼)

TDZL/RCLS Rwys 10 and 33L
REIL Rwys 15L and 33R
HIRL all rwys

NE-3, 29 OCT 2026 to 26 NOV 2026