LOC/DME I-LLM	APP CRS	Rwy Ldg 7120
111.7	317°	TDZE 102
Chan 54		Apt Elev 107

ILS or LOC RWY 32

MC ALLEN INTL (MFE)

Circling NA northeast of Rwy 14-32. ADF and DME or Radar required. When local altimeter setting not received, use Weslaco altimeter setting: increase all DA 39 feet and MDA 40 feet.

MISSED APPROACH: Climb to 2100 direct MF LOM and hold

ATIS	VALLEY APP CON	MC ALLEN TOWER ★	GND CON	UNICOM
128.5	126.55 377.2	118.5 (CTAF) L 256.9	121.8	122.95

DME or RADAR REQUIRED

ALT MISSED APCH FIX

029°
209°
113.65 HRL
R-276
Chan 83(Y)
117.2 MFE
R-029
Chan 119
SANCA
MFE 10.5

SANCA
MFE 10.5 △

LOM
MISSI
330 MF

317°
137°

MC ALLEN
117.2 MFE
Chan 119

LOCALIZER 111.7
I-LLM
Chan 54

185
OYICU
I-LLM 1.2

2100 to GASHS
130° (5.7)

317°
137°
1 min
317°

(IAF)
GASHS
I-LLM 5
RADAR

(CFBRV)

137°

MSA MF 25 NM
180°
3400
090°
2600

UNITED STATES
MEXICO

ELEV 107 | D | TDZE 102

14
32
5
TWR
81
7120 X 150
2639 X 60
0.3% UP
36

REIL Rwy 32
HIRL Rwy 14-32 L
MIRL Rwy 18-36 L

317°

2100 MF

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 53).

GASHS
I-LLM 5
RADAR

One Minute Holding Pattern

1800
137°
2100
317°

*LOC only

OYICU
I-LLM 1.2

317°

1800

GS 3.00°
TCH 50

*600 when using Weslaco altimeter setting.

*560

1.4 NM
3.8 NM

CATEGORY	A	B	C	D
S-ILS 32	302-¾ 200 (200-¾)			
S-LOC 32	560-1 458 (500-1)		560-1⅜ 458 (500-1⅜)	
CIRCLING	580-1 473 (500-1)		580-1½ 473 (500-1½)	800-2¼ 693 (700-2¼)
OYICU FIX MINIMUMS				
S-LOC 32	440-1 338 (400-1)			
CIRCLING	580-1 473 (500-1)		580-1½ 473 (500-1½)	800-2¼ 693 (700-2¼)

FAF to MAP 5.2 NM

Knots	60	90	120	150	180
Min:Sec	5:12	3:28	2:36	2:05	1:44

SC-3, 29 OCT 2026 to 26 NOV 2026
SC-3, 29 OCT 2026 to 26 NOV 2026