
TACAN	APP CRS	Rwy Ldg	8003
NIP Chan 19 (108.2)	269°	TDZE	72
		Apt Elev	80

TACAN RWY 27L
CECIL (VQQ)

VDP NA with Jacksonville Intl altimeter setting. Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Jacksonville Intl altimeter setting and increase all MDA 60 feet, increase S-27L Cats C, D, E visibility ⅛ mile.


MISSED APPROACH: Climb to 700 then climbing left turn to 2100 direct NIP TACAN and continue on NIP TACAN R-150 to WUKSO/7 DME and hold.

ATIS	JACKSONVILLE APP CON	CECIL TOWER ★	GND CON	GCO
125.275	127.775 377.075	126.1 (CTAF) L 235.625	121.625 226.675	135.075




RADAR REQUIRED

ELEV 80	TDZE 72



700	2100	NIP	NIP R-150	WUKSO NIP 7

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 67).



CATEGORY	A	B	C	D	E
S-27L	540-1 468 (500-1)		540-1⅜ 468 (500-1⅜)		
CIRCLING	540-1 460 (500-1)	560-1 480 (500-1)	600-1½ 520 (600-1½)	640-2 560 (600-2)	900-3 820 (900-3)

HIRL Rwys 9R-27L and 18L-36R L
REIL Rwys 18L, 27L L

SE-3, 29 OCT 2026 to 26 NOV 2026
SE-3, 29 OCT 2026 to 26 NOV 2026