RNAV (GPS) RWY 27

TALLAHASSEE INTL (TLH)

WAAS	APP CRS	Rwy Ldg	8000
CH 97302	275°	TDZE	58
W27A		Apt Elev	83


RNP APCH.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C or above 54°C.


ALSF-2


MISSED APPROACH: Climb to 3000 direct RAGKO and hold.

ATIS	TALLAHASSEE APP CON ★	TALLAHASSEE TOWER ★	GND CON	UNICOM
119.45 239.25	135.8 317.4	118.7 (CTAF) L 257.8	121.9 348.6	123.075



ELEV 83 TDZ 58





CATEGORY	A	B	C	D
LPV DA	258/18	200 (200-½)		
LNAV/VNAV DA	375/30	317 (300-⅝)		
LNAV MDA	480/24	422 (400-½)	480/40	422 (400-¾)
CIRCLING	580-1 497 (500-1)	600-1 517 (600-1)	640-1½ 557 (600-1½)	800-2¼ 717 (800-2¼)

TDZL/RCLS Rwy 27
REIL Rwys 9 and 18 L
HIRL Rwys 9-27 and 18-36 L

SE-3, 29 OCT 2026 to 26 NOV 2026
SE-3, 29 OCT 2026 to 26 NOV 2026