TOP ALTITUDE: ASSIGNED BY ATC

275° 095°

NOTE: Turbojet departures at/above 10000, maintain 280K until advised by ATC.

TAKEOFF MINIMUMS:
Rwys 18, 36: NA - Environmental.
Rwys 9L/R, 27L/R: Standard.

RNAV 1 - DME/DME/IRU or GPS.
RADAR required.
RADAR required for non-GPS equipped aircraft.

DETROIT DEP CON 132.35 284.0
ATIS 125.025
CLNC DEL 118.25
GND CON 121.9
PONTIAC TOWER ✱ 120.5 (CTAF)

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 9L/R: Climb on heading 095° or as assigned by ATC, thence....
TAKEOFF RUNWAYS 27L/R: Climb on heading 275° or as assigned by ATC, thence....

....for RADAR vectors to cross KZLOV at or below 15000, then on track 111° to LIDDS, then on (transition). Maintain ATC assigned altitude, expect filed altitude 10 minutes after departure.

GRIVY TRANSITION (LIDDS4.GRIVY):

LIDDS FOUR DEPARTURE (RNAV)
(LIDDS4.LIDDS) 17APR25
PONTIAC, MICHIGAN
OAKLAND COUNTY INTL (PTK)
EC-1, 29 OCT 2026 to 26 NOV 2026