RNAV (GPS) RWY 11


CENTRAL IL RGNL/BLOOMINGTON-NORMAL (BMI)


WAAS	APP CRS	Rwy Ldg	6525
CH 97617	111°	TDZE	871
W11A		Apt Elev	871


T A For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using General Downing-Peoria Intl altimeter setting. When local altimeter setting not received, use General Downing-Peoria Intl setting: increase all DA 116 feet and all MDA 120 feet; increase LPV all Cats visibility ½ mile, LNAV/VNAV all Cats and LNAV Cat C/D visibility ⅜ mile, and Circling Cats C/D visibility ¼ mile.

MISSED APPROACH: Climb to 3100 direct WAPIX and hold.

ATIS	SAINT LOUIS APP CON	BLOOMINGTON TOWER ★	GND CON	UNICOM
119.575	128.725 256.9	124.6 (CTAF) L 269.575	121.65	122.95







CATEGORY	A	B	C	D
LPV DA	1121-¾ 250 (300-¾)			
LNAV/VNAV DA	1341-1⅝ 470 (500-1⅝)			
LNAV MDA	1280-1 409 (500-1)		1280-1¼ 409 (500-1¼)	
CIRCLING	1340-1 469 (500-1)		1620-2¼ 749 (800-2¼)	1620-2½ 749 (800-2½)

TDZ/CL Rwy 20 L
HIRL Rwys 2-20 and 11-29 L

EC-3, 29 OCT 2026 to 26 NOV 2026
EC-3, 29 OCT 2026 to 26 NOV 2026