WOOLY TWO DEPARTURE (RNAV)

(WOOLY2.WOOLY) 02DEC21


WASHINGTON, DC

WASHINGTON DULLES INTL (IAD)


D-ATIS 134.85
CLNC DEL
135.7 317.8
CPDLC
GND CON
121.9 317.8 (EAST)
121.625 348.6 (WEST)
DULLES TOWER
120.1 317.8 (Rwy 1R/19L)
120.25 348.6 (Rwy 1C/19C)
134.425 348.6 (Rwys 1L/19R, 12/30)
POTOMAC DEP CON
125.05 350.2

TAKEOFF MINIMUMS:
Rwys 1L/C/R, 19L/C/R, 30:
Standard with minimum climb of 500' per NM to 820.

TOP ALTITUDE: 3000



NOTE: RNAV 1.
NOTE: DME/DME/IRU or GPS required.
NOTE: RADAR required.
NOTE: Turbojets only.



NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 1L/C/R: Climb heading 011° to 820, then on heading 011° or as assigned by ATC, expect RADAR vectors to RAZZA, thence . . . .
TAKEOFF RUNWAYS 19L/C/R: Climb heading 191° to 820, then right turn on heading 320° or as assigned by ATC, expect RADAR vectors to RAZZA, thence . . . .
TAKEOFF RUNWAY 30: Climb heading 301° to 820, then right turn on heading 320° or as assigned by ATC, expect RADAR vectors to RAZZA, thence . . . .

. . . . on track 073° to WOOLY, then on assigned transition. Maintain 3000. Expect clearance to filed altitude within ten (10) minutes after departure.

AGARD TRANSITION (WOOLY2.AGARD)
BALTIMORE TRANSITION (WOOLY2.BAL)
SWANN TRANSITION (WOOLY2.SWANN)

(WOOLY2.WOOLY) 21336
WOOLY TWO DEPARTURE (RNAV)
AL-5100 (FAA)
WASHINGTON DULLES INTL (IAD)
WASHINGTON, DC