LOC I-LBE	APP CRS	Rwy Ldg	7372
110.9	236°	TDZE	1145
		Apt Elev	1199

ILS or LOC RWY 24
ARNOLD PALMER RGNL (LBE)


RNAV 1-GPS or RADAR required for procedure entry.
From IGOCI: RNAV 1-GPS required.
RADAR required.


T A Circling NA SE of Rwy 6-24. Inop table does not apply to S-LOC 24 Cats C/D. For inop ALS, increase POSER OM minimums S-LOC 24 Cats C/D visibility to 1¾ SM.

MALSR


MISSED APPROACH: Climb to 2000 then climbing right turn to 5000 direct AGC VOR/DME and hold.

ATIS	JOHNSTOWN APP CON ★	PALMER TOWER ★	GND CON
118.375	121.2 299.2	125.0 (CTAF) L	121.8





ELEV 1199 D TDZE 1145



CATEGORY	A	B	C	D
S-ILS 24	1345-½ 200 (200-½)			
S-LOC 24	2380-¾ 1235 (1200-¾)	2380-1 1235 (1200-1)	2380-3 1235 (1200-3)	
CIRCLING	2380-1¼ 1181 (1200-1¼)	2380-1½ 1181 (1200-1½)	2380-3 1181 (1200-3)	
POSER OM MINIMUMS				
S-LOC 24	1760-½ 615 (600-½)		1760-1⅜ 615 (600-1⅜)	
CIRCLING	1760-1 561 (600-1)	1780-1 581 (600-1)	2060-2½ 861 (900-2½)	2060-2¾ 861 (900-2¾)

FAF to MAP 8.5 NM

Knots	60	90	120	150	180
Min:Sec	8:30	5:40	4:15	3:24	2:50

NE-4, 29 OCT 2026 to 26 NOV 2026
NE-4, 29 OCT 2026 to 26 NOV 2026