WAAS	APP CRS	Rwy Ldg	6001
CH 73014	034°	TDZE	624
W03A		Apt Elev	625

RNAV (GPS) RWY 3

MENOMINEE RGNL (MNM)


RNP APCH - GPS.


Baro-VNAV and VDP NA when using SUE altimeter setting. Circling Rwy 14, 32 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Rwy 3 helicopter visibility reduction below ¾ SM NA. Inop table does not apply to LPV and LNAV all Cats. When local altimeter setting not received, use SUE altimeter setting: increase LPV DA to 959 feet; increase LNAV/VNAV DA to 1209 feet and all visibilities ¼ SM; increase all MDAs 60 feet and Circling visibility Cats C and D ¼ SM. For inop ALS when using SUE altimeter setting increase LNAV MDA visibility Cat C and D to 1¼ SM. Inop table does not apply to LPV all Cats and LNAV Cats A and B when using SUE altimeter setting.

MALSR


MISSED APPROACH: Climb to 2300 direct UCINI and hold.

AWOS-3PT	GREEN BAY APP CON ★	UNICOM
121.45	120.3 338.2	122.8 (CTAF) L





CATEGORY	A	B	C	D
LPV DA	900-1 276 (300-1)			
LNAV/VNAV DA	1150-1 526 (600-1)			
LNAV MDA	1000-1 376 (400-1)			
CIRCLING	1200-1 575 (600-1)		1200-1½ 575 (600-1½)	1380-2½ 755 (800-2½)



EC-1, 29 OCT 2026 to 26 NOV 2026
EC-1, 29 OCT 2026 to 26 NOV 2026