WAAS CH 90417 W11A	APP CRS 114°	Rwy Ldg 8099 TDZE 539 Apt Elev 544

RNAV (GPS) RWY 11


ST LOUIS RGNL (ALN)


RNP APCH.


Rwy 11 helicopter visibility reduction below ¾ SM NA.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C.

MISSED APPROACH: Climb to 2100 direct QUNIE and hold.

ATIS	ST LOUIS APP CON	REGIONAL TOWER*	GND CON	UNICOM
128.0	124.2 353.9	126.0 (CTAF) L 239.0	120.2	122.95







CATEGORY	A	B	C	D
LPV DA	794-⅞ 255 (300-⅞)			
LNAV/VNAV DA	881-1⅛ 342 (400-1⅛)			
LNAV MDA	980-1 441 (500-1)		980-1⅜ 441 (500-1⅜)	
CIRCLING	1000-1 456 (500-1)		1160-1¾ 616 (700-1¾)	1200-2 656 (700-2)

REIL Rwy 11 L
HIRL Rwy 11-29 L
MIRL Rwy 17-35 L

EC-3, 29 OCT 2026 to 26 NOV 2026
EC-3, 29 OCT 2026 to 26 NOV 2026