ILS or LOC/DME RWY 34

ARLINGTON MUNI (GKY)

LOC/DME I-GKY	APP CRS	Rwy Ldg	6080
111.55	342°	TDZE	620
Chan 52 (Y)		Apt Elev	628

When local altimeter setting not received, use Grand Prairie Muni altimeter setting. Inop table does not apply to S-ILS 34. For inop MALSR increase S-LOC 34 Cat A, B visibility to 1 mile.

MALSR

MISSED APPROACH: Climb to 1100 then climbing left turn to 3000 via heading 245° and TTT VOR/DME R-206 to TILLA INT/TTT 37 DME and hold.

ASOS	LONE STAR APP CON	ARLINGTON TOWER ★	GND CON	CLNC DEL	CLNC DEL
127.375	135.975 379.9	128.625 (CTAF) (L)	121.875	121.875	118.85 (When twr closed)

RADAR REQUIRED

ALTERNATE MISSED APCH FIX

115.7 FUZ Chan 104
113.1 TTT Chan 78
117.7 MQP Chan 124
116.2 CVE Chan 109
015°
195°
R-213
R-119
R-206
R-195
TILLA TTT 37

113.1 TTT Chan 78
R-206

LOCALIZER 111.55
I-GKY
Chan 52(Y)

MYKES
I-GKY 5.4
RADAR

830
2000
(6)
342°

(IF)
ESIKE
I-GKY 11.4
RADAR

2300
(5)
342°

(IAF)
WIKEB
I-GKY 16.4
RADAR

162°

MSA TTT 25 NM
2700
090°
270°
3600

MISSED APCH FIX

115.7 FUZ Chan 104
113.1 TTT Chan 78
117.7 MQP Chan 124
116.2 CVE Chan 109
026°
206°
R-213
R-119
R-206
R-195
TILLA TTT 37

ELEV 628 TDZE 620

16 (d)
6080 X 100
0.5% UP (P)
34 (A5)
342°
TWR

MIRL Rwy 16-34
REIL Rwy 16

1100	3000 hdg 245°	TTT R-206	TILLA △

*LOC only.

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 55).

MYKES
I-GKY 5.4
RADAR

ESIKE
I-GKY 11.4
RADAR

*I-GKY
I-GKY 2.4
I-GKY 1.1

2000
342°
2300
2000

GS 3.00°
TCH 60

1.3 NM 2.9 NM 6 NM

CATEGORY	A	B	C	D
S-ILS 34	820-¾ 200 (200-¾)			NA
S-LOC 34	1060-¾ 440 (500-¾)			NA
CIRCLING	1100-1 472 (500-1)	1140-1 512 (600-1)	1220-1½ 592 (600-1½)	NA

SC-2, 29 OCT 2026 to 26 NOV 2026
SC-2, 29 OCT 2026 to 26 NOV 2026