WAAS CH 63230 W17A | APP CRS 173° | Rwy Ldg 5501 | TDZE 592 | Apt Elev 592

RNAV (GPS) RWY 17
MC GREGOR EXEC (PWG)

RNP APCH - GPS.

ASR

Baro-VNAV NA when using Waco Rgnl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C. When local altimeter setting not received, use Waco Rgnl altimeter setting and increase LPV DA to 873 feet and all visibilities ⅛ SM; increase LNAV/VNAV DA to 873 feet and all visibilities ⅛ SM; increase all MDAs 40 feet and Circling visibility Cat C ¼ SM.

MISSED APPROACH: Climb to 2500 direct ZUDIS and on track 095° to SATTY and hold.

AWOS-3PT	WACO APP CON★	UNICOM
135.525	127.65 352.0	123.05 (CTAF) L

1296

(IAF) IGORR

3000 NoPT 136° (12.1)

4 NM

173° 353°

(IF/IAF) IMJUC

2000 (6) 173°

(FAF) BLDEE

RW17

ZUDIS

(15.3) 095°

3000 NoPT 239° (17.3) (IAF) IMIPE

Procedure NA for arrivals at IMIPE on V15-54 northeast bound.

MSA RW17 25 NM

3600

MISSED APCH FIX

4 NM 136° 316° SATTY

ELEV 592 TDZE 592

173°

4 NM Holding Pattern

IMJUC

3000 353° 173°

BLDEE

2000

173°

1.3 NM to RW17

RW17

2000

GP 3.00° TCH 37

6 NM 3 NM 1.3 NM

2500	ZUDIS	tr 095°	SATTY

5501 X 75 0.4% UP

3484 X 55

17 35

CATEGORY	A	B	C	D
LPV DA	842-¾	250 (300-¾)		NA
LNAV/VNAV DA	842-¾	250 (300-¾)		NA
LNAV MDA	1040-1	448 (500-1)	1040-1⅜ 448 (500-1⅜)	NA
CIRCLING	1040-1 448 (500-1)	1060-1 468 (500-1)	1300-2 708 (800-2)	NA

MIRL Rwy 17-35 L

REIL Rwy 17 L

SC-3, 29 OCT 2026 to 26 NOV 2026
SC-3, 29 OCT 2026 to 26 NOV 2026