CHARLOTTE SIX DEPARTURE

CHARLOTTE DEP CON
128.325 307.8
AWOS-3P
118.175
CLNC DEL
127.35

RADAR and DME required.

TOP ALTITUDE: 3000

NALEY

NOTE: Transponder code will be issued via CLT Clearance Delivery.
NOTE: Turboprops: Operate in a manner that will result in best forward speed and climb rate.
NOTE: Turbojet aircraft accelerate to 250K, if unable, advise ATC. Upon reaching 10000 MSL, accelerate to and maintain 280K, if unable, advise ATC.

KRITR

TAKEOFF MINIMUMS
Rwy 2: Standard.
Rwy 20: Standard with minimum climb of 233'/NM to 2200.

BOBZY
NEANO
ESTRR
DEBIE
BRCHM
PEKNN
LAMDE
LILLS
KWEEN
BEAVY
ANDYS
HAMLN

MSA RUQ 25 NM
3400

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF ALL RUNWAYS: Climb on assigned heading for vectors to assigned route. Maintain 3000, expect filed altitude 10 minutes after departure.

SE-2, 29 OCT 2026 to 26 NOV 2026
SE-2, 29 OCT 2026 to 26 NOV 2026