ILS or LOC RWY 6

BROOKHAVEN (HWV)


LOC I-HWV	APP CRS	Rwy Ldg	4201
108.95	059°	TDZE	77
		Apt Elev	81


Rwy 6 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use ISP altimeter setting and increase S-ILS 6 DA to 367; increase all MDAs 40 feet. For inop ALS, increase S-ILS 6 all Cats visibility to ⅞ SM and increase S-LOC 6 all Cats visibility to 1 SM. ILS localizer unusable 0.5 NM to threshold. Circling Rwy 6,15 NA at night.


MALSR

MISSED APPROACH: Climb to 600 then climbing right turn to 2000 on heading 270° and CCC VOR/DME R-227 to MAIDS OM/INT and hold, continue climb-in-hold to 2000.

ASOS	NEW YORK APP CON	UNICOM
119.625	120.05 343.75	122.8 (CTAF) L







CATEGORY	A	B	C	D
S-ILS 6	339-¾	262 (300-¾)	NA	
S-LOC 6	540-¾	463 (500-¾)	NA	
CIRCLING	560-1	479 (500-1)	NA	

REIL Rwys 15, 24 and 33 L
MIRL Rwys 6-24 and 15-33 L

FAF to MAP 4.4 NM					
Knots	60	90	120	150	180
Min:Sec	4:24	2:56	2:12	1:46	1:28

NE-2, 29 OCT 2026 to 26 NOV 2026
NE-2, 29 OCT 2026 to 26 NOV 2026