RNAV (GPS) RWY 21

FOOTHILLS RGNL (MRN)


WAAS CH 40322 W21A	APP CRS 211°	Rwy Ldg 5500 TDZE 1270 Apt Elev 1270


RNP APCH - GPS.

T A Baro-VNAV and VDP NA when using HKY altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. Rwy 21 helicopter visibility reduction below ¾ SM NA. When local altimeter not received, use HKY altimeter setting and increase LPV DA to 1562 feet; LNAV/VNAV DA to 1642 feet; increase all MDAs 60 feet and visibility LNAV Cats C and D and Circling Cat D ¼ SM.


MISSED APPROACH: Climb to 2000 then climbing right turn to 4500 direct CIKIS and hold.

AWOS-3P	ATLANTA CENTER	UNICOM
124.175	125.15 263.0	122.7 (CTAF) L





MIRL Rwy 3-21 L
REIL Rwys 3 and 21 L



CATEGORY	A	B	C	D
LPV DA	1520-1		250 (300-1)	
LNAV/VNAV DA	1600-1		330 (400-1)	
LNAV MDA	1680-1	410 (500-1)	1680-1⅛	410 (500-1⅛)
CIRCLING	1720-1 450 (500-1)	1760-1 490 (500-1)	1800-1½ 530 (600-1½)	2140-2¾ 870 (900-2¾)

SE-2, 29 OCT 2026 to 26 NOV 2026
SE-2, 29 OCT 2026 to 26 NOV 2026