WAAS	APP CRS	Rwy Ldg	5000
CH 70426	329°	TDZE	336
W33A		Apt Elev	336

RNAV (GPS) RWY 33
WARRENTON/FAUQUIER (HWY)

DME/DME RNP-0.3 NA. When local altimeter setting not received, use Culpeper altimeter setting; increase all MDA 40 feet, increase LP Cat C/D visibility ⅛ SM, increase LNAV Cat C/D and Circling Cat D visibility ¼ SM.

MISSED APPROACH: Climb to 800 then climbing left turn to 3000 direct CSN VORTAC and hold, continue climb in hold to 3000.

AWOS-3PT	POTOMAC APP CON	UNICOM
120.35	128.525 306.925	122.7 (CTAF) L

RADAR REQUIRED

WASHINGTON DC METROPOLITAN SFRA

WARNING -- WASHINGTON DC SFRA. CONTACT POTOMAC APP CON

CASANOVA CSN

4 NM 207° 027°

RW33

LRGNT 2.5 NM to RW33

476 (A) 469

329°

(FAF) CRLYN

2000 335° (6.5)

(IF/IAF) ANTNY

145° 325°

4 NM

R-6608A

R-6608B

DEMO 1 MOA

MSA RW33 25 NM 4700

NoPT for arrival at ANTNY on V286 northwest bound.

ELEV 336 TDZE 336

370 ±

15

0.5% UP

5000 X 100

33

329°

REIL Rwys 15 and 33
HIRL Rwy 15-33 L

Procedure NA when DEMO 1 MOA active.

800 3000 CSN

4 NM Holding Pattern

CRLYN ANTNY

LRGNT 2.5 NM to RW33

1.1 NM to RW33

RW33

329° 2000 335° 145° 325° 2000

1160

3.00°

TCH 45

1.1 NM 1.4 NM 2.6 NM 6.5 NM

CATEGORY	A	B	C	D
LP MDA	720-1 384 (400-1)		720-1⅛ 384 (400-1⅛)	
LNAV MDA	740-1 404 (500-1)		740-1⅛ 404 (500-1⅛)	
CIRCLING	760-1 424 (500-1)	800-1 464 (500-1)	880-1½ 544 (600-1½)	980-2 644 (700-2)

NE-3, 29 OCT 2026 to 26 NOV 2026
NE-3, 29 OCT 2026 to 26 NOV 2026