WAAS CH 61116 W08A	APP CRS 087°	Rwy Ldg 4400 TDZE 894 Apt Elev 894

RNAV (GPS) RWY 8


LAKEFIELD (CQA)


RNP APCH - GPS.


T NA Rwy 8 helicopter visibility reduction below ¾ SM NA. Baro-VNAV NA. Use AXV altimeter setting; when not received, use DAY altimeter setting and increase LPV DA to 1293 feet; increase LNAV/VNAV DA to 1350 feet and all visibilities ⅛ SM; increase all MDAs 80 feet and LNAV visibility Cat C ⅛ SM and Circling visibility Cat C ¼ SM.

MISSED APPROACH: Climb to 3000 direct EVOZU and on track 127° to ICREB and hold.

AXV AWOS-3PT	COLUMBUS APP CON	UNICOM	
128.325	134.45 352.05	122.8 (CTAF)	123.3 L







CATEGORY	A	B	C	D
LPV DA	1221-1¼ 327 (400-1¼)			NA
LNAV/VNAV DA	1278-1¼ 384 (400-1¼)			NA
LNAV MDA	1440-1 546 (600-1)		1440-1⅝ 546 (600-1⅝)	NA
CIRCLING	1440-1 546 (600-1)		1520-1¾ 626 (700-1¾)	NA

REIL Rwys 8 and 26 L
MIRL Rwy 8-26 L

EC-2, 29 OCT 2026 to 26 NOV 2026
EC-2, 29 OCT 2026 to 26 NOV 2026