CHARLOTTE SIX DEPARTURE

CHARLOTTE DEP CON
120.05 307.8
AWOS-3
120.825
GCO
121.725

RADAR and DME required.

TOP ALTITUDE: 3000

NALEY

NOTE: Transponder code will be issued via CLT Clearance Delivery.
NOTE: Turboprops: Operate in a manner that will result in best forward speed and climb rate.
NOTE: Turbojet aircraft accelerate to 250K, if unable, advise ATC. Upon reaching 10000 MSL, accelerate to and maintain 280K, if unable, advise ATC.

KRITR

TAKEOFF MINIMUMS
Rwy 6: Standard with minimum climb of 268'/NM to 700.
Rwy 24: Standard with minimum climb of 275'/NM to 700.

BOBZY
NEANO
ESTRR
DEBIE
BRCHM
PEKNN
LAMDE
LILLS
KWEEN
BEAVY
ANDYS
HAMLN
MSA LKR 25 NM
2300

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF ALL RUNWAYS: Climb on assigned heading for vectors to assigned route. Maintain 3000, expect filed altitude 10 minutes after departure.

SE-2, 29 OCT 2026 to 26 NOV 2026
SE-2, 29 OCT 2026 to 26 NOV 2026