RNAV (GPS) RWY 3


ST CLAIR COUNTY (PLR)


WAAS	APP CRS	Rwy Ldg	4771
CH 70540	026°	TDZE	484
W03A		Apt Elev	485


DME/DME RNP-0.3 NA. VDP NA when using Anniston altimeter setting. Rwy 3, helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Anniston altimeter setting and increase all DA 63 feet and all visibility ¼ SM, increase all MDA 80 feet and LNAV Cat C/D visibility ⅛ SM and Circling Cat C/D ¼ SM.

MISSED APPROACH: Climb to 1200, then climbing left turn to 4000 direct HANUR and hold, continue climb-in-hold to 4000.

AWOS-3P	BIRMINGHAM APP CON	CLNC DEL	UNICOM
119.625	123.8 256.8	121.725 (GCO)	123.05 (CTAF) L







CATEGORY	A	B	C	D
LPV DA	835-1⅛ 351 (400-1⅛)			
LNAV MDA	1140-1 656 (700-1)		1140-1⅞ 656 (700-1⅞)	
CIRCLING	1180-1 695 (700-1)		1240-2¼ 755 (800-2¼)	1340-2¾ 855 (900-2¾)

SE-4, 29 OCT 2026 to 26 NOV 2026
SE-4, 29 OCT 2026 to 26 NOV 2026