ILS or LOC RWY 5

BESSEMER NTL (EKY)

LOC/DME I-EKY	APP CRS	Rwy Ldg	6007
111.75	053°	TDZE	700
Chan 54 (Y)		Apt Elev	700

NA

When local altimeter setting not received, use Alabaster altimeter setting and increase DA 41 feet, increase all MDAs 60 feet; increase S-LOC 5 Cat C visibility ⅛ SM and Cat D visibility ¼ SM, increase Circling Cat C visibility ⅛ SM Cat D visibility ¼ SM, increase JURAM fix S-LOC 5 Cat C visibility ⅛ SM and Cat D visibility ¼ SM; increase Circling Cat D visibility ¼ SM. VDP NA with Alabaster altimeter setting.

MISSED APPROACH: Climb to 1200 then climbing left turn to 3000 direct OKW VORTAC and hold.

AWOS-3PT	BIRMINGHAM APP CON	CLNC DEL	UNICOM
118.825	124.9 351.85	123.75	123.0 (CTAF) L

ALTERNATE MISSED APCH FIX

VULCAN
VUZ 114.4
Chan 91
R-230 050° 230°

Procedure NA for arrivals at OKW VORTAC via V66 westbound.

IAF
BROOKWOOD
111.0 OKW
Chan 47

JURAM
I-EKY 2.8
792

MEATA INT
I-EKY 6.2

LOCALIZER 111.75
I-EKY
Chan 54(Y)

R-275 095° 275°
R-086
2500
115°
(7.9)
2400
053°
(6.4)
R-115
233°
(IF)
KHANN INT
I-EKY 12.6
OKW 7.9

MSA OKW 25 NM
3700

Procedure Turn NA
KHANN INT
I-EKY 12.6

#1260 when using Alabaster altimeter setting.

1200	3000	OKW

MEATA INT
I-EKY 6.2

JURAM
I-EKY 2.8

*I-EKY 2.2

I-EKY 1.2

* LOC only

2500
053°
2400
GS 3.00°
TCH 60
2400
#*1200

6.4 NM | 3.4 NM | 0.6 NM | 1.1 NM

ELEV 700 TDZE 700

6007 X 100

053°

HIRL Rwy 5-23 L
REIL Rwys 5 and 23 L

CATEGORY	A	B	C	D
S-ILS 5	900-¾ 200 (200-¾)			
S-LOC 5	1200-1	500 (500-1)	1200-1⅜ 500 (500-1⅜)	1200-1½ 500 (500-1½)
CIRCLING	1200-1	500 (500-1)	1220-1½ 520 (600-1½)	1320-2 620 (700-2)
JURAM FIX MINIMUMS				
S-LOC 5	1100-1	400 (400-1)	1100-1⅛ 400 (400-1⅛)	1100-1¼ 400 (400-1¼)
CIRCLING	1200-1	500 (500-1)	1220-1½ 520 (600-1½)	1320-2 620 (700-2)

FAF to MAP 5.1 NM

Knots	60	90	120	150	180
Min:Sec	5:06	3:24	2:33	2:02	1:42

SE-4, 29 OCT 2026 to 26 NOV 2026
SE-4, 29 OCT 2026 to 26 NOV 2026