WAAS CH 82714 W22A	APP CRS 217°	Rwy Ldg 5001 TDZE 465 Apt Elev 468

AL-6386 (FAA)

RNAV (GPS) RWY 22

BENTON COUNTY (ØM4)


RNP APCH.


T NA


Baro-VNAV NA. Rwy 22 helicopter visibility reduction below 1 SM NA. Use Beech River Rgnl altimeter setting; when not received, use Jackson altimeter setting and increase all DA 58 feet and all MDA 60 feet and increase LPV all Cats visibility ¼ mile, LNAV/VNAV all Cats visibility ¼ mile, and LNAV Cat C visibility ¼ mile. Procedure NA at night.

MISSED APPROACH: Climb to 2500 direct TEMSE and hold.

PVE AWOS-3	MEMPHIS CENTER	UNICOM
118.125	125.85 379.25	122.8 (CTAF) L







CATEGORY	A	B	C	D
LPV DA	833-1¼ 368 (400-1¼)			NA
LNAV/VNAV DA	980-1¾ 515 (600-1¾)			NA
LNAV MDA	1080-1 615 (700-1)		1080-1¾ 615 (700-1¾)	NA

MIRL Rwy 4-22
REIL Rwys 4 and 22 L

SE-1, 29 OCT 2026 to 26 NOV 2026
SE-1, 29 OCT 2026 to 26 NOV 2026