RNAV (GPS) RWY 18

MCKINNEY NTL (TKI)

WAAS CH 87102 W18A	APP CRS 179°	Rwy Ldg 7002 / TDZE 576 / Apt Elev 589

DME/DME RNP-0.3 NA. VDP NA with Dallas Love Fld altimeter setting. When local altimeter setting not received, use Dallas Love Fld altimeter setting and increase all DA 70 feet and all MDA 80 feet, increase LNAV Cats C and D ⅛ mile, and Circling Cats C and D visibility ¼ mile. For inop MALSR when using Dallas Love Fld altimeter setting increase LPV all Cats visibility to 1 mile.

MALSR

MISSED APPROACH: Climb to 3000 direct ONEME and hold.

ATIS	LONE STAR APP CON	MC KINNEY TOWER ★	GND CON	CLNC DEL	UNICOM
119.925	124.3 282.275	118.825 (CTAF) L	121.875	121.35 (When twr closed)	122.95

RADAR REQUIRED

(IAF) SASIE
3000
167° (4.6)
(IF) VELCI
(IAF) KARLA
3000
258° (9.2)
2300
179° (6)
(FAF) IKOTY
LIRNE 2.5 NM to RW18
729±
669±
RW18
MISSED APCH FIX ONEME
359°
179°
4 NM
MSA RW18 25 NM
3800

ELEV 589 | TDZE 576

179°
8 L
TWR
7002 X 150
36
HIRL Rwy 18-36 L

3000 | ONEME
*LNAV only.
LIRNE 2.5 NM to RW18
*0.9 NM to RW18
RW18
IKOTY
2300
VELCI
3000
179°
1420*
2300
GP 3.00°
TCH 50
0.9 NM | 1.6 NM | 2.8 NM | 6 NM

CATEGORY	A	B	C	D
LPV DA	776-½ 200 (200-½)			
LNAV MDA	920-½ 344 (400-½)		920-⅝ 344 (400-⅝)	
CIRCLING	1040-1 451 (500-1)	1120-1 531 (600-1)	1200-1¾ 611 (700-1¾)	1380-2½ 791 (800-2½)

SC-2, 29 OCT 2026 to 26 NOV 2026
SC-2, 29 OCT 2026 to 26 NOV 2026