RNAV (GPS) RWY 36

MCKINNEY NTL (TKI)

WAAS	APP CRS	Rwy Ldg	7002
CH 49202	359°	TDZE	589
W36A		Apt Elev	589

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -8°C (18°F) or above 54°C (130°F). When local altimeter setting not received, use Dallas Love Fld altimeter setting and increase all DA 70 feet and all MDA 80 feet, and increase LNAV/VNAV all Cats visibility ⅛ mile, LNAV Cat C/D and Circling Cat C/D visibility ¼ mile. DME/DME RNP-0.3 NA. VDP and Baro-VNAV NA when using Dallas Love Fld altimeter setting. For inop MALS increase LNAV/VNAV all Cats visibility to ⅞ mile and LNAV Cat D visibility to 1 mile. For inop MALS when using Dallas Love Fld altimeter setting increase LPV all Cats visibility to ⅞ mile, LNAV/VNAV Cat D visibility to 1⅛ mile, and LNAV Cat D visibility to 1¼ mile. Inop table does not apply to LPV all Cats.

MALS

MISSED APPROACH: Climb to 3000 direct VELCI and hold.

ATIS	LONE STAR APP CON	MC KINNEY TOWER ★	GND CON	CLNC DEL	UNICOM
119.925	124.3 282.275	118.825 (CTAF) L	121.875	121.35 (When twr closed)	122.95

RADAR REQUIRED

MISSED APCH FIX

4 NM 359° 179° VELCI

RW36 689±

WAXUX 2.5 NM to RW36 732

(FAF) ILEZY

2000 359° (6)

(IF) ONEME

MSA RW36 25 NM 3800

3000 004° (25.9)

3000 340° (28.7)

(IAF) TACKE

(IAF) BACKS

ELEV 589 TDZE 589

8 L

TWR

7002 X 150

36

359°

HIRL Rwy 18-36 L

ONEME 3000 359° ILEZY 2000 2000

WAXUX 2.5 NM to RW36 *0.9 NM to RW36 RW36 *1420

3000 VELCI *LNAV only.

GP 3.00° TCH 50

6 NM 1.8 NM 1.6 NM 0.9 NM

CATEGORY	A	B	C	D
LPV DA	789-¾	200 (200-¾)		
LNAV/VNAV DA	850-¾	261 (300-¾)		
LNAV MDA	940-¾	351 (400-¾)		
CIRCLING	1120-1	531 (600-1)	1200-1¾ 611 (700-1¾)	1380-2½ 791 (800-2½)

SC-2, 29 OCT 2026 to 26 NOV 2026

SC-2, 29 OCT 2026 to 26 NOV 2026