LOC I-AEG	APP CRS	Rwy Ldg	7398
110.1	215°	TDZE	5817
		Apt Elev	5837

ILS or LOC RWY 22
DOUBLE EAGLE II (AEG)

T A NA — When local altimeter setting not received, use Albuquerque Intl Sunport altimeter setting and increase all DA 94 feet, increase all MDA 100 feet, and increase visibility S-LOC 22 Cats C/D ¼ mile, Circling Cats C/D ½ mile. For inop MALSR when using Albuquerque Intl Sunport altimeter setting, increase visibility S-ILS 22 all Cats ⅜ mile.

MALSR

MISSED APPROACH: Climb to 6500 then climbing right turn 7700 direct DUDLE LOM and hold.

ATIS	ALBUQUERQUE APP CON	DOUBLE EAGLE II TOWER ★	GND CON
119.025	127.4 253.5	120.15 (CTAF) L	121.625

ADF REQUIRED

AWASH

035°

(CFVLF)

1 min

215°

LOM/IAF
DUDLE
351 AE

LOCALIZER 110.1
I-AEG

5886±

8000
9000
7000

ALTERNATE MISSED APCH FIX
AWASH
136°
316°
110.6 SAF
R-238
Chan 43
113.2 ABQ
R-316
Chan 79

7900
013°
(11.5)

MSA AE 25 NM
180°
8100
11900
360°

ALBUQUERQUE
113.2 ABQ
Chan 79

ELEV 5837 TDZE 5837

215°

TWR

17

0.4% UP

7398 X 100

5983 X 100

35

REIL Rwys 17 and 35 L
MIRL Rwys 4-22 and 17-35 L

FAF to MAP 5.5 NM					
Knots	60	90	120	150	180
Min:Sec	5:30	3:40	2:45	2:12	1:50

6500	7700	AE

AE LOM 7629

One Minute Holding Pattern

035° 7700

215°

215° 7700

GS 3.00°
TCH 55

5.5 NM

CATEGORY	A	B	C	D
S-ILS 22	6017-½ 200 (200-½)			
S-LOC 22	6140-½ 323 (400-½)			
CIRCLING	6400-1 563 (600-1)		6420-1½ 583 (600-1½)	6640-2½ 803 (900-2½)

SW-1, 29 OCT 2026 to 26 NOV 2026
SW-1, 29 OCT 2026 to 26 NOV 2026