MAYNR THREE DEPARTURE (RNAV)

(MAYNR3.MAYNR) 31OCT24

POMPANO BEACH AIRPARK (PMP)

POMPANO BEACH, FLORIDA

MIAMI DEP CON
126.05 251.1
ATIS
120.55
GND CON
121.9
POMPANO BEACH TOWER★
125.4 (CTAF)

RNAV 1 - DME/DME/IRU or GPS.
From SLIPT to MAXIM: RNAV 1- GPS.
From SLIPT to CANOA: RNAV 1- GPS.

RADAR required for non-GPS equipped aircraft.
RADAR required.

TOP ALTITUDE: ASSIGNED BY ATC

TAKEOFF MINIMUMS
Rwys 6, 10, 15, 24, 28, 33: Standard with minimum climb of 500'/NM to 520.

MSA PMP 25 NM
2900

NOTE: Jet aircraft only.
NOTE: Accelerate to 250K until leaving 10000, if unable, advise ATC.

AUSTI
5000

202°
(26)

MAYNR

15800
*1300
243°
(29)

MCLAW

FL180
*1300
265°
(36)

SLIPT

FL180
*1300
250°
(40)

JABOX

FL180
*1300
261°
(41)

CANOA

232°
FL180
*1300
(15)

MAXIM

FL180
*1300
185°
(34)

FUNDI

N

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

(MAYNR3.MAYNR) 24305

MAYNR THREE DEPARTURE (RNAV)

AL-5972 (FAA)

POMPANO BEACH AIRPARK (PMP)

POMPANO BEACH, FLORIDA

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 6, 10, 15, 24, 28, 33: Climb on heading assigned by ATC for vectors to cross AUSTI at or above 5000, thence. . . .

. . . .on track 202° to MAYNR, then on assigned transition, maintain ATC assigned altitude. Expect clearance to filed altitude within 10 minutes after departure.

CANOA TRANSITION (MAYNR3.CANOA)
FUNDI TRANSITION (MAYNR3.FUNDI)
MAXIM TRANSITION (MAYNR3.MAXIM)

SE-3, 26 NOV 2026 to 24 DEC 2026