

**OWYHEE** (10U) 4 W UTC-8(-7DT) N41°57.22' W116°10.92'

SALT LAKE CITY

5377 B NOTAM FILE RNO

**RWY 05-23:** H4700X60 (ASPH) MIRL

**RWY 05:** REIL. PAPI(P2L)—GA 3.0° TCH 44'.

**RWY 23:** REIL. PAPI(P2L)—GA 3.0° TCH 44'.

**SERVICE:** LGT ACTIVATE REIL Rwy 05 and Rwy 23; PAPI Rwy 05 and Rwy 23 and MIRL Rwy 05-23—CTAF.

**AIRPORT REMARKS:** Unattended. Bird act invof arpt. Tie-down chains not prvdd. 3 hel prkg pads adj to main ramp.

**AIRPORT MANAGER:** 208-759-3100

**WEATHER DATA SOURCES:** AWOS-3 118.525 (208) 258-0383.

**COMMUNICATIONS:** CTAF 122.9

**CLEARANCE DELIVERY PHONE:** For CD ctc Salt Lake ARTCC at 801-320-2568.

## PAHRUMP

**CALVADA MEADOWS** (74P) 5 N UTC-8(-7DT) N36°16.32' W115°59.72'

LAS VEGAS

2726 NOTAM FILE RNO

L-7D

**RWY 15-33:** H4081X48 (ASPH-GRVL-AFSC) LIRL 1.0% up SE

**RWY 15:** Thld dsplcd 200'. P-line.

**RWY 33:** Bldg.

**SERVICE:** FUEL 100LL LGT ACTIVATE LIRL Rwy 15-33—CTAF.

**AIRPORT REMARKS:** Unattended. PPR for acft ops over 12500 lbs., coml ops, and for gldr, pwrld prcht, banner towing, parachuting, flt trng, UAS, or jet ops. Tsnt acft parking off NW parl twy at trml. Acft wingspans exceeding Group I (49 ft) rstrd NW parl twy and all taxilanes.

**AIRPORT MANAGER:** (775) 910-9289

**COMMUNICATIONS:** CTAF/UNICOM 122.8

**CLEARANCE DELIVERY PHONE:** For CD ctc Los Angeles ARTCC at 661-575-2079.

**RADIO AIDS TO NAVIGATION:** NOTAM FILE LAS.

**LAS VEGAS (H) VORTACW** 116.9 LAS Chan 116 N36°04.78' W115°09.59' 271° 42.2 NM to fld. 2136/15E.

No NOTAM MP: 1600-1800Z± Sat

VOR unusable:

025°-160° byd 20 NM blo 6,000'

160°-200° byd 20 NM blo 9,000'

200°-025° byd 25 NM blo 11,000'

200°-220° byd 15 NM blo 9,000'

220°-245° byd 35 NM blo 15,000'

245°-260° byd 35 NM blo 14,000'

260°-275° byd 35 NM blo 14,000'

275°-310° byd 35 NM blo 16,500'

TACAN AZIMUTH unusable:

025°-160° byd 20 NM blo 6,000'

160°-200° byd 20 NM blo 9,000'

200°-025° byd 25 NM blo 11,000'

200°-220° byd 15 NM blo 9,000'

220°-245° byd 35 NM blo 15,000'

245°-260° byd 35 NM blo 14,000'

260°-275° byd 35 NM blo 14,000'

275°-310° byd 35 NM blo 16,500'

DME unusable:

025°-160° byd 20 NM blo 6,000'

160°-200° byd 20 NM blo 9,000'

200°-025° byd 25 NM blo 11,000'

200°-220° byd 15 NM blo 9,000'

220°-245° byd 35 NM blo 15,000'

245°-260° byd 35 NM blo 14,000'

260°-275° byd 35 NM blo 14,000'

275°-310° byd 35 NM blo 16,500'

• • • • •  
**HELIPAD H1:** H20X20 (CONC)