

LOUISVILLE MUHAMMAD ALI INTL (SDF)(KSDP) P (ANG) 4 S UTC-5(-4DT) N38°10.45'

ST LOUIS

W85°44.19'

H-5E, 10F, L-27E

501 B LRA Class I, ARFF Index C NOTAM FILE SDF

IAP, AD

RWY 17R-35L: H11887X150 (CONC-GRVD) S-75, D-207, 2D-360, 2D/2D2-850 PCN 71 R/B/W/T HIRL CL

RWY 17R: MALSR. TDZL. PAPI(P4L)—GA 3.0° TCH 75'. RVR-TMR Thld dspcd 846'.

RWY 35L: ALSF2. TDZL. PAPI(P4L)—GA 3.0° TCH 75'. RVR-TMR Thld dspcd 1040'.

RWY 17L-35R: H8579X150 (CONC-GRVD) S-75, D-207, 2D-360, 2D/2D2-850 PCN 71 R/B/W/T HIRL CL

RWY 17L: MALSR. TDZL. PAPI(P4L)—GA 3.32° TCH 71'. RVR-TMR Thld dspcd 328'. 0.4% down.

RWY 35R: ALSF2. TDZL. PAPI(P4R)—GA 3.0° TCH 72'. RVR-TMR Thld dspcd 449'.

RWY 11-29: H7250X150 (CONC-WC) S-75, D-170, 2D-360, 2D/2D2-850 PCN 71 R/B/W/T HIRL

RWY 11: PAPI(P4L)—GA 3.0° TCH 65'. RVR-R Bldg.

RWY 29: MALSR. PAPI(P4L)—GA 3.0° TCH 56'. RVR-T

RUNWAY DECLARED DISTANCE INFORMATION

RWY 11: TORA-7250 TODA-7250 ASDA-6946 LDA-6946

RWY 17L: TORA-8579 TODA-8579 ASDA-8129 LDA-7800

RWY 17R: TORA-11095 TODA-11095 ASDA-11095 LDA-10000

RWY 29: TORA-7250 TODA-7250 ASDA-7250 LDA-7250

RWY 35L: TORA-11290 TODA-11290 ASDA-11290 LDA-10000

RWY 35R: TORA-8579 TODA-8579 ASDA-8250 LDA-7800

SERVICE: S4 FUEL 100LL, JET A, A+ QX 4 MILITARY—JASU 2(MC-1A) 3(MC-2A) 7(A/M32A-86) 3(AM32-95). FUEL A, A+ (C502-368-1515) (NC-100LL)

AIRPORT REMARKS: Attended continuously. Continuous const on arprt, be alert for freq rwy and twy closures. Birds on and invof arprt. ASDE-X in use. Operate transponders with altitude reporting mode and ADS-B (if equipped) enabled on all airport surfaces. Acft tail hgt 65 ft or greater require 24 hr PPR. Line up and wait waiver in effect from SS until SR at the int of Rwy 17R at Twy B or Rwy 17R at Twy A8. Line up and wait waiver in effect from SS until SR at the int of Rwy 35L at Twy B or Rwy 35L at Twy A. Std departure points on Rwy 17R are at Twy B and Rwy 17R at Twy A8. Pilots must req use of Rwy 17R extn. Declared distance for tkf at Twy B ASDA/TORA/TODA 10,245'. Std departure points on Rwy 35L are at Twy A and Twy B. Pilots must req use of Rwy 35L extn. Declared distance for tkf at Twy A and Twy B ASDA/TORA/TODA 10,250'. Flight Notification Service (ADCUS) avbl.

MILITARY REMARKS: ANG: Duty hr 1200-2000Z (1300-2100-DT) Mon-Thur, 1200-1800Z (DT 1300-1900Z) Fri. Apvl auth 123 AW/OGC, Base Ops DSN 741-4581/4584, C502-413-4581/4584. Ctc Derby Ops for eng start and taxi clnc. FAA GP 6 acft rqr min 24 hr notice for PPR.

AIRPORT MANAGER: 502-380-8200

WEATHER DATA SOURCES: ASOS (502) 367-1492 LLWAS. TDWR.

COMMUNICATIONS: D-ATIS 118.725 UNICOM 122.95

Ⓡ APP CON 134.15 123.675 (WEST) 132.075 (EAST)

Ⓡ DEP CON 123.675 132.075

TOWER 124.2 GND CON 121.7 CLNC DEL 126.1

CPDLC (LOGON KUSA)

PDC

AIRSPACE: CLASS C svc ctc APP CON.

VOR TEST FACILITY (VOT) 111.0

RADIO AIDS TO NAVIGATION: NOTAM FILE LOU.

(H) VORTACW 114.8 IIU Chan 95 N38°06.21' W85°34.65' 298° 8.6 NM to fld. 721/1E.

VOR portion unusable:

001°-094° blo 10,000'

230°-284° blo 10,000'

285°-339° blo 7,000'

340°-360° byd 20 NM blo 5,000'

LAANG NDB (LOMW) 414 LK N38°08.69' W85°38.00' 294° 5.2 NM to fld. 613/4W. NOTAM FILE SDF.

ILS/DME 111.95 I-PKI Chan 56(Y) Rwy 17L. Class IE.

ILS/DME 110.3 I-SNU Chan 40 Rwy 17R. Class IE.

LOC 109.1 I-LKS Rwy 29. LOM LAANG NDB. LOC unusable byd 19° r and left of course.

ILS/DME 109.35 I-RLI Chan 30(Y) Rwy 35L. Class IIIE.

ILS/DME 110.55 I-JJM Chan 42(Y) Rwy 35R. Class IIIE.

