

PHILADELPHIA INTL (PHL)(KPHL) 5 SW UTC-5(-4DT) N39°52.33' W75°14.44'

36 B LRA Class I, ARFF Index E NOTAM FILE PHL Not insp.

RWY 09R-27L: H12000X200 (ASPH-GRVD) S-200, D-210, 2D-350

PCN 60 F/A/X/T HIRL CL

RWY 09R: ALSF2. TDZL. PAPI(P4R)—GA 3.0° TCH 72'. RVR-TMR Tree.

RWY 27L: MALSR. PAPI(P4L)—GA 3.0° TCH 73'. RVR-TMR Thld dsplcd 1913'. Boat.

RWY 09L-27R: H9500X150 (ASPH-GRVD) S-100, D-210, 2D-350

PCN 60 F/A/X/T HIRL CL

RWY 09L: MALSR. REIL. RVR-TMR Trees.

RWY 27R: MALSR. PAPI(P4L)—GA 3.0° TCH 81'. RVR-TMR Boat.

RWY 17-35: H6500X150 (ASPH-GRVD) S-100, D-170, 2S-175,

2D-300 PCN 27 F/A/X/T HIRL

RWY 17: MALSF. PAPI(P4L)—GA 3.0° TCH 50'. RVR-TR Sign.

RWY 35: REIL. PAPI(P4L)—GA 3.15° TCH 52'. RVR-TR Boat.

RWY 08-26: H5001X150 (ASPH-GRVD) D-145 PCN 27 F/A/X/T

HIRL CL 0.5% up E

RWY 08: RVR-TR Bldg.

RWY 26: MALSR. PAPI(P4R)—GA 3.15° TCH 50'. RVR-TR Trees.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 08: TORA-5001 TODA-5001 ASDA-5001 LDA-5001

RWY 09L: TORA-9500 TODA-9500 ASDA-9500 LDA-9500

RWY 09R: TORA-12000 TODA-12000 ASDA-12000 LDA-12000

RWY 17: TORA-6500 TODA-6500 ASDA-6500 LDA-6500

RWY 26: TORA-5001 TODA-5001 ASDA-5001 LDA-5001

RWY 27L: TORA-12000 TODA-12000 ASDA-11825 LDA-9912

RWY 27R: TORA-9500 TODA-9500 ASDA-9500 LDA-8864

RWY 35: TORA-6500 TODA-6500 ASDA-6500 LDA-6500

SERVICE: S4 FUEL 100LL, JET A OX 1, 2, 3, 4 LGT Rwy 26 PAPI unusable byd 8° right of cntrln.

NOISE: Arpt is lctd in a noise sensitive area. Arpt noise abatement takeoff procedures are to be used.

AIRPORT REMARKS: Attended continuously. Birds on and in/ov arpt. Unlgtg stack 288' MSL (271' AGL) 2.3 NM southwest of arpt. TCAS equipped acft, TCAS alert may be caused by transponder equipped ships lctd PHL Naval Base 3 NM east. Rwy 26, Rwy 27L, Rwy 27R, and Rwy 35 ship channel (Delaware River) max height of ships 189'. Rwy 26 ship channel (Schuylkill) max height of ships 149'. Rwy 27R LDA 9500' avbl O/R to ATC. Possible unmarked ship obst transiting east or westbound along the Delaware River reaching heights of 189', be alert when apch PHL Rwy 35 and whenever circling or visually apch all other rwys. Pilots can exp to exit and re-enter the PHL Class B airspace dur moderate to heavy arrival periods. Rwy 09R rollout RVR used for Rwy 09L midpoint RVR. ASDE-X in use. Operate transponders with altitude reporting mode and ADS-B (if equipped) enabled on all airport surfaces. Only nose-in parking permitted on North remote aprons. PPR from arpt ops for all acft parking on remote aprons, ctc 215-937-6914/6800. Land Rwy 26, tkf Rwy 08. Ldg fee. Flight Notification Service (ADCUS) avbl.

AIRPORT MANAGER: 215-937-6914

WEATHER DATA SOURCES: ASOS (215) 492-9617 LLWAS. TDWR.

COMMUNICATIONS: D-ATIS ARR 133.4 D-ATIS DEP 135.925 UNICOM 122.95

Ⓡ APP CON 123.8 (001°-089° at or blo 5000') 126.85 (270°-360° at or blo 5000') 127.35 (090°-269° at or blo 5000') 128.4 (270°-089° avb 5000') 133.875 (090°-269° 8000' -6000')

Ⓡ DEP CON 119.75 (090°-269°) 124.35 (270°-089°)

TOWER 118.5 (Rwys 09L-27R, 17-35, 08-26) 135.1 (Rwy 09R-27L) GND CON 121.9 121.65


CLNC DEL 118.85

CPDLC (LOGON KUSA)

PDC

AIRSPACE: CLASS B See VFR Terminal Area Chart.

VOR TEST FACILITY (VOT) 109.8



WASHINGTON

H-101, 121, L-34G, A

IAP, AD

CONTINUED ON NEXT PAGE

PENNSYLVANIA

CONTINUED FROM PRECEDING PAGE

RADIO AIDS TO NAVIGATION: NOTAM FILE MIV.

DUPONT (L) VORTAC 114.0 DQO Chan 87 N39°40.69' W75°36.43' 065° 20.6 NM to fld. 70/10W.

DME unusable:
210°-235° byd 30 NM blo 3,000'
235°-265° byd 22 NM

VOR unusable:
230°-265° byd 22 NM

TACAN AZIMUTH unusable:
001°-050° byd 7 NM
210°-235° byd 30 NM blo 3,000'
235°-265° byd 22 NM

ILS/DME 108.95 I-VII Chan 26(Y) Rwy 09L. Class IE. DME also serves Rwy 27R. DME unusable byd 12.3 NM blw 3,000'.

ILS/DME 109.3 I-PHL Chan 30 Rwy 09R. Class IIIE. DME also serves Rwy 27L.

ILS/DME 108.75 I-MYY Chan 24(Y) Rwy 17. Class IT. LOC unusable byd 15° left of course.

ILS/DME 111.55 I-LLH Chan 52(Y) Rwy 26.

ILS/DME 109.3 I-GLC Chan 30 Rwy 27L. Class IE.

ILS/DME 108.95 I-PDP Chan 26(Y) Rwy 27R. Class IIE. DME installed on Rwy 09L serves Rwy 09L/27r.

WINGS FLD (LOM)(KLOM) 3 NW UTC-5(-4DT) N40°08.25' W75°15.91'

NEW YORK

302 B NOTAM FILE LOM

L-34G, A

RWY 06-24: H3700X75 (ASPH) S-12.5 MIRL 0.6% up SW

IAP

RWY 06: REIL. PAPI(P2L)—GA 3.0° TCH 40'. Thld dspcd 177'. Pole.

RWY 24: REIL. PAPI(P2L)—GA 3.0° TCH 40'. Trees.

SERVICE: S4 FUEL 100LL, JET A OX 1, 2 LGT Dusk-Dawn. ACTVT
MIRL Rwys 06-24, PAPI and REIL Rwy 06 and 24—CTAF.

NOISE: Noise abatement Rwy 06 and 24, no turns after tkof before 1000' AGL. Avoid overflight of schools east and west of arpt. Rwy 06-24 no touch and go landings.

AIRPORT REMARKS: Attended 1100-0300Z±. Deer and large flocks of geese on and in/ov arpt. For svc after hrs ctc 215-646-0400. PPR all acct exceeding 12,500 lbs max tkf gross weight or abv, call 215-646-0400.

AIRPORT MANAGER: 215-646-0400

WEATHER DATA SOURCES: AWOS-3 118.925 (215) 646-1068.

COMMUNICATIONS: CTAF/UNICOM 123.0

® **PHILADELPHIA APP/DEP CON** 126.85

CLNC DEL 118.55 (800-354-9884)


CLEARANCE DELIVERY PHONE: For CD ctc Philadelphia Apch at 800-354-9884.

RADIO AIDS TO NAVIGATION: NOTAM FILE IPT.

MODENA (L) VORTACW 113.2 MXE Chan 79 N39°55.08' W75°40.25' 064° 22.9 NM to fld. 473/9W.

VOR unusable:
036°-046°
047°-057° byd 10 NM
058°-085°
170°-248° byd 27 NM blo 7,500'
170°-248° byd 30 NM blo 9,500'
170°-248° byd 8 NM blo 6,000'
268°-278° byd 28 NM
278°-290° blo 10,000'
290°-326°

AMBLER NDB (MHW) 275 ING N40°07.56' W75°17.11' 065° 1.2 NM to fld. 12W.
OTS indef



PHILADELPHIA SPB (See ESSINGTON on page 273)