

MIDLAND INTL AIR AND SPACE PORT (MAF)(KMAF) 8 SW UTC-6(-5DT) N31°56.55' W102°12.12' SAN ANTONIO
 2872 B LRA ARFF Index—See Remarks NOTAM FILE MAF MON Airport H-6G, L-6H
 RWY 16R-34L: H9501X150 (ASPH-GRVD) S-160, D-200, 2S-175, IAP, AD

2D-350, 2D/2D2-700 PCN 53 F/B/X/T HIRL

RWY 16R: PAPI(P4L)—GA 3.0° TCH 50'.

RWY 34L: REIL. PAPI(P4L)—GA 3.0° TCH 50'. Pole.

RWY 10-28: H8302X150 (ASPH-GRVD) S-160, D-200, 2S-175, 2D-350, 2D/2D2-700 PCN 53 F/B/X/T HIRL

RWY 10: MALS. PAPI(P4L)—GA 3.0° TCH 54'. RVR-T

RWY 28: MALS. PAPI(P4R)—GA 3.0° TCH 53'. RVR-R Thld displcd 691'.

RWY 04-22: H4605X75 (ASPH) S-30, D-60 PCN 19 F/B/X/T MIRL

RWY 04: Pole.

RWY 22: Road.

RWY 16L-34R: H4247X100 (ASPH) S-30, D-60 PCN 19 F/B/X/T

MIRL 0.4% up N

RWY 16L: Fence.

RWY 34R: Road.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 04: TORA-4605 TODA-4605 ASDA-4605 LDA-4605

RWY 10: TORA-8302 TODA-8302 ASDA-8302 LDA-8302

RWY 16L: TORA-4247 TODA-4247 ASDA-4247 LDA-4247

RWY 16R: TORA-9501 TODA-9501 ASDA-9501 LDA-9501

RWY 22: TORA-4605 TODA-4605 ASDA-4605 LDA-4605

RWY 28: TORA-8302 TODA-8302 ASDA-8302 LDA-7610

RWY 34L: TORA-9501 TODA-9501 ASDA-9501 LDA-9501

RWY 34R: TORA-4247 TODA-4247 ASDA-4247 LDA-4247

SERVICE: S4 FUEL 100LL, JET A, A1 OX 2, 4 LGT When twr closed HIRL Rwy 10-28 and 16R-34L preset on med ints, MIRL Rwy 04-22 and 16L-34R preset on med ints during expected IFR conditions only. When twr closed ACTIVATE MALS Rwy 10 and MALS Rwy 28—CTAF.

AIRPORT REMARKS: Attended continuously. Bird activity on and in/ov arpt. Rwy 04-22 and 16L-34R clsd to acft over 60,000 pounds. Rwy 10-28 E 692' CLOSED to acft over 60,000 lbs. Rwy 16R-34L 180° turn prohibited to acft 60,000 pounds and above. Rwy 10-28 180° turn prohibited to acft 60,000 pounds or above. Taxiways B and F north Rwy 10-28 clsd to acft over 60,000 pounds. Numerous oil rigs in/ov arpt at or blo 200' AGL. Class I ARFF Index C, for ARFF services between 0600-1200Z daily ctc FSS at 800-992-7433. U.S. Customs user fee arpt. Ldg fee. Space Launch Activity Area - See Special Notices. All runup pads are LTD usage to ACFT 60000 LBS & BLW. ACR OPS are prohibited on Rwy 16L-34R and Rwy 04-22. OPRS on non paved SFC are prohibited WO 24 HR PPR.

AIRPORT MANAGER: 432-560-2200

WEATHER DATA SOURCES: ASOS (432) 561-5935 LLWAS.

COMMUNICATIONS: CTAF 118.7 ATIS 126.8 UNICOM 122.95

RCO 122.6 (SAN ANGELO RADIO)

Ⓡ APP/DEP CON 124.6 (241°-136°) 121.1 (137°-240°) (1200-0600Z‡)

Ⓡ FORT WORTH CENTER APP/DEP CON 133.1 (0600-1200Z‡)

TOWER 118.7 (1200-0600Z‡) GND CON 121.9 CLNC DEL 118.05

CLEARANCE DELIVERY PHONE: For CD if una to ctc on FSS freq, ctc Fort Worth ARTCC at 817-858-7584.

AIRSPACE: CLASS C svc ctc APP CON svc (per TWR/NOTAM 1200-0600Z‡); other times CLASS E.

VOR TEST FACILITY (VOT) 108.2

RADIO AIDS TO NAVIGATION: NOTAM FILE MAF.

(L) VORTACW 114.8 MAF Chan 95 N32°00.56' W102°11.42' 177° 4.0 NM to fld. 2860/11E.

VOR unusable:

010°-020° byd 8 NM blo 8,000'

FARLY NDB (HW/LOM) 326 MA N31°59.29' W102°19.51' 104° 6.9 NM to fld. 2957/9E. NDB unmonitored when ATCT clsd.

ILS/DME 110.3 I-MAF Chan 40 Rwy 10. Class IE. LOM FARLY NDB. ILS/DME unmonitored when ATCT clsd.

ASR (1200-0600Z‡)

